

Splashproof double horizontal surface-mounting box with one M20 input for two functions, white

701-84801

4 year
warranty

This double horizontal surface-mounting box with one M20 input is suitable for two functions. The entire unit is splashproof which makes it extremely well-suited for use in damp areas and in demanding environments. Finishing colour: white

Technical data

Splashproof double horizontal surface-mounting box with one M20 input for two functions, white.

- Function: The fixation points of this double, horizontal box are situated 50 mm apart on the vertical axis and 71 mm apart on the horizontal axis. This size indication is indelibly imprinted on the bottom of each box. The oval screw openings allow for imprecise drilling. By forming a pressure lock, a gasket ensures the protection degree and the double insulation. The box contains two diagonal, knockout condensation openings.
- Number of mechanisms: 2
- Material surface-mounting box: The surface-mounting box is made of impact-resistant, dust-resistant, halogen-free and self-extinguishing polypropylene (UL94-V2/1.6 mm).
- Protection degree: See protection degree of the mounted function
- Impact resistance: The combination of a Hydro mechanism and a flush- or surface-mounting box has an impact resistance of IK07 with a minimum temperature of -25 °C and a maximum temperature of 55 °C
- Colour: white (coloured in mass, approximately NCS S 0502 - Y50R, RAL 9010)
- Certification marks: CEBEC, SEMKO, VDE, DEMKO, NF, KEMA, ÖVE
- Marking: CE

