

# Splashproof blind plate, grey

700-38500

4 year  
warranty

This blind plate is mounted directly onto a splashproof mounting box and made of ABS. It is used to cleanly close off connection points for later system expansions or to install non-standard functions. Finishing colour: grey.

## Technical data

Splashproof blind plate, grey. Protection lid: Each socket outlet is covered entirely by a hinged protection cap which opens upward. A spring and a hook-fastener keep the protection cap tightly closed.

- Colour: The base material is coloured light grey in mass (approximately NCS S 1502 - B, RAL 7035)
- Sealing: The cover has an integral closure and is hermetically sealed onto the appropriate box.
- Number of mechanisms: 1
- Material finishing: The blind plate is made of impact-resistant, dust-resistant, halogen-free and self-extinguishing polypropylene (UL94-V2/1.6 mm). The blind plate itself is made of rigid ABS.
- Surface-mounting box: The function is designed to be mounted in a splashproof mounting box. The function has an integral closure and is hermetically sealed onto the appropriate box (to be ordered separately).
- Chemical resistance: ammonia-rich environments may cause faster ageing of the base
- Ambient temperature: -25 – +55 °C
- Protection degree: IP55 for the combination of a function and a splashproof mounting box
- Impact resistance: The combination of a Hydro mechanism and a flush- or surface-mounting box has an impact resistance of IK07 with a minimum temperature of -25 °C and a maximum temperature of 55 °C
- Marking: CE

