

# Splashproof double horizontal wall socket with pin earthing, shutters and plug-in terminals; includes surface-mounting box with two inputs on the upper side, black

761-37754

4 year warranty

With this horizontal combination, the two splashproof surface-mounting wall sockets are equipped with pin earthing, shutters and plug-in terminals. Both wall sockets are also equipped with a hinged protective cover and are pre-wired (2.5 mm<sup>2</sup>) and mounted in a double splashproof surface-mounting box with two inputs on the upper side. The entire unit is splashproof which makes it extremely well-suited for use in damp areas and in demanding environments. Colour combination: black.

Wires that remain fixed:

- wire is fixed firmly due to the high-quality plug-in terminal with a long life span, tested according to the norm
- since the conductor release on the mechanisms is located at the front, the wiring cannot push on the release when you place it in the box

Faster and easier installation:

- all connections terminals are located at the top of the base:
  - to ensure all wires can be cut and stripped at the same length
  - to guarantee more space under the mechanism, so you can easily fold the wires and place the mechanism in the box without the wiring pushing it back up.

Niko quality:

- long life span since the plug-in terminal stays within the limits of the norm during a temperature and power drop

## Technical data

Splashproof double horizontal wall socket with pin earthing, shutters and plug-in terminals; includes surface-mounting box with two inputs on the upper side, black.

- Number of mechanisms: 2
- Cable space
  - 15.7 mm wiring space under the mechanism
  - mechanism is held by 2 laterally positioned holders in the box
  - a snap connector holds the wired mechanism in place
- Wire connection
  - contact buses fitted with plug-in terminals for clamping the wires
  - manual release or release with a screwdriver from the front side
- Wire capacity
  - all connection terminals at the top side of the base
  - up to 2 x 2.5 mm<sup>2</sup> wire per terminal
- Stripping length
  - 12 mm stripping length
  - indelibly indicated at the rear side: stripping length and wiring diagram
  - indelibly indicated at the front side: terminals and switch symbol
- Chemical resistance: ammonia-rich environments may cause faster ageing of the base



**niko**

- Protection degree: IP55 for the combination of a socket outlet and a splashproof mounting box
- Impact resistance: The combination of a Hydro mechanism and a flush- or surface-mounting box has an impact resistance of IK07 with a minimum temperature of -25 °C and a maximum temperature of 55 °C
- Colour: The base material is coloured in mass, black (RAL 9005)
- Certification marks: CEBEC, NF
- Marking: CE

$\frac{h}{2}$   $\frac{16}{250}$  A Vac

