

Twofold faceplate with 71 mm centre distance, Niko Pure steel white coated

154-76800

4 year
warranty

Twofold faceplate with 71 mm centre distance from the range Niko Pure. Niko Pure steel white coated

Technical data

Twofold faceplate with 71 mm centre distance, Niko Pure steel white coated.

- Double faceplate for two switches.
- Colour: enamelled steel white (approximately NCS S 1002 - B50G, RAL 000 90 00)
- Frame composition: It consists of an upper frame and lower frame that are mechanically interconnected.
- Material upperframe: The upperframe is made of steel.
- Material lower frame: The lower frame is made of white polycarbonate (PC) + acrylic-styrene-acrylate (ASA), white coated
- Frame thickness: The upper frame is 2 mm thick and the lower frame 6 mm.
- Centre-to-centre distance: 71 mm
- Surface-mounting height: max. 8.5 mm
- Fire safety
 - self-extinguishing: complies with a filament test of 650°C
 - halogen-free
- Protection degree: IP41 for the combination of a mechanism, central plate and faceplate
- Impact resistance: The combination of a mechanism, a central plate and a faceplate has an impact-resistance of IK06
- Dimensions (HxWxD): 83 x 154 x 8.9 mm
- Dimensions visible (HxWxD): 83 mm
- Certification marks: CEBEC, KEMA, ÖVE, SEMKO, NF
- Marking: CE

