

# Splashproof threefold vertical surface-mounting box with one double M20 input for three functions, black

761-84302

4 year warranty

This threefold vertical surface-mounting box with one double M20 input is suitable for three functions. The entire unit is splashproof which makes it particularly suitable for use in damp areas and in demanding environments. Finishing colour: black

## Technical data

Splashproof threefold vertical surface-mounting box with one double M20 input for three functions, black.

- Function: The fixation points are situated 195 mm apart on the vertical axis. There are two additional fixation point situated at a distance of 50 mm from the exterior points (also on the vertical axis). This size indication is indelibly imprinted on the bottom of each box. The oval screw openings allow for imprecise drilling. By forming a pressure lock, a gasket ensures the protection degree and the double insulation. The box contains two diagonal, knockout condensation openings.
- Number of mechanisms: 3
- Material surface-mounting box: The surface-mounting box is made of impact-resistant, dust-resistant, halogen-free and self-extinguishing polypropylene (UL94-V2/1.6 mm).
- Protection degree: See protection degree of the mounted function
- Impact resistance: The combination of a Hydro mechanism and a flush- or surface-mounting box has an impact resistance of IK07 with a minimum temperature of -25 °C and a maximum temperature of 55 °C
- Colour: The base material is coloured in mass, black (RAL 9005)
- Certification marks: CEBEC, SEMKO, VDE, DEMKO, NF, KEMA, ÖVE
- Marking: CE



CE