

Electronic 70W transformer with terminal connections on the primary side (2x) and a wire connection on the secondary side

320-00102

4 year warranty

This electronic transformer has a capacity of 70W and is universally dimmable. It is suitable for the connection of low-voltage loads (12 V). On the primary side, the two inputs make interconnection easy (max. 8x). The Teflon wire on the secondary side can be directly connected to a low voltage lamp. The easy-to-mount click cap ensures strain relief. The transformer is extremely compact and is therefore very well-suited for installation in small spaces. This transformer is also suitable for flush mounting in furniture. It is equipped with an integrated thermal protection and an integrated protection against short-circuit, overload and overheating. This transformer has an IP20 protection degree.



Technical data

Electronic 70W transformer with terminal connections on the primary side (2x) and a wire connection on the secondary side

- Function: electronic transformer
- Input voltage: 230 Vac \pm 10 %, 50 Hz
- Dimensions (HxWxD): 116 x 52 x 32 mm
- Primary wire connection: Fourfold primary terminal connection: 1 x 2.5 mm² or 2 x 1.5 mm² per screw terminal
- Secondary wire connection: teflon wire (200 °C): 2 x 0.75 mm², length 30 cm
- Number of exits (pairs): 1
- Maximum wire length secondary connection: 2 m
- Output voltage: 11.5 Vac, 35 kHz
- Minimum load: 20 W
- Maximum load: 70 W
- Maximum ambient temperature: +50 °C
- Maximum housing temperature (T_c): 80 °C
- Minimum drill diameter: 55 mm
- Minimum free space in false ceiling: 100 mm
- Application: suitable for flush-mounting in furniture
- Mounting method: flush-mounting
- Safety protections: self-resetting, built-in protection against short-circuit, overload and overheating
- Fire safety
 - self-extinguishing: complies with a filament test of 850 °C
 - suitable for normal combustible surfaces
- Protection degree: IP20
- Protection class: Class III device: SELV (safety extra low voltage), suitable as a power supply for class III loads
- Finishing colour: white
- Material upperframe: plastic
- Certification marks: ENEC
- Marking: CE



Dimensions

