

# 24 V push button, Niko Invisible, anthracite coated

122-10001

4 year  
warranty

This push button in Niko Invisible design can be connected as onefold, double or fourfold push button and can serve different functions: on/off, motor control, dimming or smart home functions.

The default position of the four control keys is at the top, bottom, left and right side of the push button. A simple 45-degree rotation can shift the keys to the top left, top right, bottom left and bottom right instead. This allows for a more intuitive control of, for example, a duo of rolling shutters. The control keys are not indicated on the push button to safeguard the minimalistic design of the product.

The push button is equipped with subtle LED lighting that elegantly illuminates the contour of the push button. The LED offers four levels of light intensity: off (0), a faint glow that is just visible in dark rooms like a bedroom (1), a brighter glow that is visible in normally lit rooms like a living room (2 – default setting) and a bright glow that subtly lights up the surrounding area and can be used for staircase or corridor lighting (3).

A professional can customise the finishing set to coordinate with or blend into its surrounding surface for an ultra-minimalist look. It can be covered with any wallpaper and paint colour. And thanks to its enamelled finishing in the colour anthracite coated, you can even use it without any covering.


Dedicated Niko Invisible installation kits are available for brickwork and plasterboard, as well as a hole saw that facilitates application in plasterboard surfaces.

- Minimalist architectural design
- Blends into the wall
- Only a signature circular outline is visible
- Niko quality
- Homogenous backlighting
- Four light intensity settings

## Technical data

24 V push button, Niko Invisible, anthracite coated.

- Number of control buttons: 4 control buttons
- LED colour: white
- Colour temperature: 2700 K (warm white)
- Protection degree: IP41
- Impact resistance: After mounting, an impact-resistance of IK06 is guaranteed.
- Material base
  - impact-resistant, dust-proof and dimensionally stable polycarbonate
  - light grey RAL 7035
- Flush mounting depth: 19.7 mm
- Fixing method
  - with screws for simple fixing in a flush-mounting box with grip surfaces
- Wire connection



**niko**

- the sockets are equipped with screw terminals for clamping the wires.
- Lighting element
  - the base is fitted with 5 LEDs that, combined, offer four levels of light intensity: off (0), a faint glow that is just visible in the dark but doesn't disturb sleeping, for use in bedrooms (1), a brighter glow that is visible in normally lit rooms like a living room (2) and a bright glow that subtly lights up the surrounding area (3)
  - the light intensity can be adjusted at the front of the base using a slotted screwdriver.
- Ambient temperature: -5 – +40 °C
- Dimensions (HxWxD): 74 x 74 x 29 mm
- Dimensions visible (HxWxD): 70 x 70 x 0 mm
- Weight: 53.2 g
- Marking: CE



### Dimensions

