

# Threefold faceplate, 60 mm centre distance, vertical, Niko Pure steel white coated

154-76300

4 year  
warranty

Threefold faceplate with 60 mm centre-to-centre distance, vertical, from the range Niko Pure. Niko Pure steel white coated

## Technical data

Threefold faceplate, 60 mm centre distance, vertical, Niko Pure steel white coated.

- Threefold faceplate for three switches.
- Colour: enamelled steel white (approximately NCS S 1002 - B50G, RAL 000 90 00)
- Frame composition: It consists of an upper frame and lower frame that are mechanically interconnected.
- Material upperframe: The upperframe is made of steel.
- Material lower frame: The lower frame is made of white polycarbonate (PC) + acrylic-styrene-acrylate (ASA), white coated.
- Frame thickness: The upper frame is 2 mm thick and the lower frame 6 mm.
- Centre-to-centre distance: 60 mm
- Surface-mounting height: max. 8.5 mm
- Fire safety
  - self-extinguishing: complies with a filament test of 650°C
  - halogen-free
- Protection degree: IP41 for the combination of a mechanism, central plate and faceplate
- Impact resistance: The combination of a mechanism, a central plate and a faceplate has an impact-resistance of IK06
- Dimensions (HxWxD): 203 x 83 x 8.9 mm
- Dimensions visible (HxWxD): 203 mm
- Certification marks: CE, NF, ÖVE, KEMA
- Marking: CE

