

Niko dimmer switch for Hue system, Niko Intense matt black

130-91004


4 year warranty

With this wireless and battery-free dimmer switch, you can operate the Philips Hue lamps effortlessly. Determine in the Philips Hue app what each button must do (switching on and off, dimming, activating scene settings). Mechanism including push button and faceplate Niko Intense matt black. Philips Hue Bridge v2 required and not included.

Technical data

Niko dimmer switch for Hue system, Niko Intense matt black.

- Dimensions (HxWxD): 83 x 83 x 15 mm
- Power supply: integrated kinetic energy Harvester
- RF protocol: Zigbee (green power)
- Mounting height: 110 cm
- Temperature (storage / operating): -25 up to +65 °C
- The maximum temperature difference between the Niko dimmer switch and a receiver should not exceed 60 °C
- Maximum range (indoor): Up to 20 m
- Operating frequency: 2,4 GHz (2402 to 2480 MHz)
- Number of configurable switches: 4
- Humidity: 0 – 95 % relative humidity, non condensing
- Maximum RF power: 7 dBm / 5 mW
- Configuration: Philips Hue app
- Antenna: integrated antenna
- Protection degree: IP20
- Weight: 45.6 g
- Battery: no
- Marking: CE



Base voor the Niko dimmer switch for Hue System.

- Marking: CE

Double key, for wireless dimmer switch (Hue®, Bluetooth®, EnOcean®, KNX®), black coated.

- Number of control buttons: 2 control buttons
- Material central plate: The central plate is enamelled and made of rigid PC and ASA.
- Colour: enamelled black
- Dismantling: To dismantle simply pull the central plate off the mechanism.
- Protection degree: IP20
- Impact resistance: After mounting, an impact-resistance of IK06 is guaranteed.
- Fire safety
 - The plastic parts of the central plate are self-extinguishing (comply with a filament test of 650°C)
 - The plastic parts of the central plate are halogen-free.
- Dimensions of finishing: 45 x 45 mm (HxW)
- Dimensions (HxWxD): 44.5 x 44.5 x 8.6 mm
- Marking: CE

Single faceplate Niko Intense matt black.

- Simple faceplate for one switch.
- Recommended colour central plate: Niko recommends a design combination with a black coated central plate (colour code 161).
- Frame composition: It consists of an upper frame and lower frame that are mechanically interconnected.
- Material upperframe: The upperframe is made from impact-resistant, dimensionally stable polycarbonate.
- Surface-mounting height: max. 8.5 mm
- Fire safety
 - self-extinguishing: complies with a filament test of 650°C
 - halogen-free
- Dimensions (HxWxD): 85 x 85 x 8.9 mm
- Certification marks: CEBEC, ÖVE, KEMA, VDE, NF, SEMKO
- Marking: CE

