

Presence detector, Niko Home Control, 9.5 m, IP65, mini, for flush mounting, white & black

550-20220

4 year warranty

The mini detector detects movement and changes in light intensity. Using this information various Niko Home Control actions can be activated or deactivated. The product is suitable for indoor ceiling mounting in suspended ceilings. Black deco ring included. Finishing colour: white & black

- The detection range can be reduced from 360° to 180° using the cover cap supplied, which is clicked into place on the detector.
- Fits discretely into every interior thanks to its small format and the black and white cover cap.
- Three applications in one: absence or presence detector and photo cell.
- Users are free to adjust the light sensitivity and switch-off delay in the user settings software and app.



Detection range



H	A	B	C
	Across	Towards	Presence
2 m	Ø 6 m	Ø 3 m	Ø 2 m
2.5 m	Ø 8 m	Ø 3.7 m	Ø 2.5 m
3 m	Ø 9.5 m	Ø 4.5 m	Ø 3 m

niko

Technical data

Article number	550-20220
Input voltage	26 Vdc (SELV, safety extra-low voltage)
Detector output	26 V
Light intensity range	2 lux – 25000 lux
Detection angle	360°
Detection range (PIR)	ø 9.5 m from a height of 3 m
Ambient temperature	-10 – +50 °C
Mounting method	flush-mounting
Mounting height	2 – 3 m
Drill diameter	30 mm
Dimensions visible (HxWxD)	36 x 36 x 13.3 mm
Dimensions (HxWxD)	36 x 36 x 62.6 mm
Protection degree	IP65
Marking	CE

Dimensions

