

Twofold faceplate, vertical 60 mm centre distance, for a socket outlet and one 45x45 function, Niko Rocker and Niko Toggle alu grey brushed

155-74202

4 year warranty

The Niko Rocker and Niko Toggle twofold vertically oriented faceplate clicks onto a socket outlet and one 45 x 45 mm function that have been vertically installed on top of each other with a centre distance of 60 mm. The faceplate combines with any available Niko Rocker and Niko Toggle socket outlet finishing set and a Niko 45 x 45 mm function. It consists of an upper frame, light guide and lower frame that are mechanically interconnected. The upper frame is made of brushed aluminium. The lower frame is made of dark grey polycarbonate (PC) + acrylic-styrene-acrylate (ASA). The upper frame is 6 mm thick and the lower frame 2 mm.


Niko recommends a design combination with a finishing set in the following colour: alu grey for Niko Rocker and Niko Toggle finishing sets and anthracite coated for other finishing sets.

- Exclusive materials
- Authentic vintage design
- Belgian design & craftsmanship
- Design matches Niko Pure portfolio
- Proven Niko quality
- Designed to fit the standard socket outlet base
- Designed to fit any available 45 x 45 mm function

Technical data

Twofold faceplate, vertical 60 mm centre distance, for a socket outlet and one 45x45 function, Niko Rocker and Niko Toggle alu grey brushed.

- Double faceplate for two switches.
- Colour: alu grey (approximately NCS S 2002 - G, RAL 000 80 00)
- Recommended colour central plate: alu grey for Niko Rocker and Niko Toggle finishing sets and anthracite coated for other finishing sets
- Frame composition: It consists of an upper frame, light guide and lower frame that are mechanically interconnected.
- Material upper frame: The upper frame is made of brushed aluminium.
- Material lower frame: The lower frame is made of dark grey polycarbonate (PC) + acrylic-styrene-acrylate (ASA).
- Frame thickness: The upper frame is 6 mm thick and the lower frame 2 mm.
- Centre-to-centre distance: 60 mm
- Impact resistance: The combination of a mechanism, a central plate and a faceplate has an impact resistance of IK06
- Dimensions (HxWxD): 143 x 83 x 13 mm
- Dimensions visible (HxWxD): 143 x 83 mm
- Marking: CE



niko

CE

www.niko.eu

niko

155-74202 - 02-07-2025