

Presence detector, KNX®, 2 channels, 14 m, for flush-mounting box

351-25033

4 year
warranty

Master/secondary presence detector for universal use thanks to versatile accessories. daylight control for 2 zones, 1 secondary zone (ON/OFF), HVAC, light threshold and switch-off delay adjustable during operation, orientation light, automatic and semi-automatic mode. The detector has an integrated light sensor and is KNX® compatible only.



- Combination of master/secondary possible
- Can be placed at a height of up to 6 metres

Presence detector for use in standard rooms such as offices, meeting rooms, etc.

- Everything can be programmed using ETS software
- Very simple programming
- Can be programmed as a presence or absence detector
- 2 channels for heliometer setting with standby lighting
 - 1 channel for turning the lighting on and off
 - 1 channel for turning the HVAC installation on and off

Technical data

Article number	351-25033
Configuration	master/secondary
Input voltage	30 Vdc via KNX®-bus
Detector output	KNX®
Maximum power consumption	0.3 W
Maximum current consumption	10 mA
Light intensity range	10 lux – 2000 lux
Number of channels	2 channels
Switch-off delay	1 s – 24 min
Detection angle	360°
Detection range (PIR)	ø 14 m from a height of 3 m
Ambient temperature	-20 – +40 °C
Mounting method	flush-mounting
Mounting height	2 – 6 m
Dimensions (HxWxD)	88 x 88 x 50 mm
Impact resistance	IK02
Modification of settings	ETS software
Marking	CE

Dimensions

