

Mood control

The mood control allows the resident to create different mood settings for different occasions. A mood setting is a combination of settings with regard to lighting, roll-down shutters, sun blinds, etc.



Mood control

The mood control allows the resident to create different mood settings for different occasions. A mood setting is a combination of settings with regard to lighting, roll-down shutters, sun blinds, etc.

- recommended mounting height: 120 - 150 cm
- flush-mounting depth: 20 mm
- dimensions: 45 x 45 x 32 mm (HxWxD)
- resting potential: 26 Vdc (SELV, safety extra-low voltage)
- back-lit colour display with three buttons
- ambient temperature: 0 - 50 °C




COMPLETE UNIT

| | | |
|------------------|-----------|---|
| 550-13040 | Pieces: 6 | For mounting with claws, centre distance 60 mm |
| 550-13041 | Pieces: 6 | For screw fixing |
| 550-13042 | Pieces: 6 | For mounting with screws, centre distance 60 mm |

550-13040

4 year warranty

Mood control Niko Home Control



This control is connected directly to the installation and is used to set and call up a desired mood. Moods can also be automatically called up using sensors. This control is mounted in a flush-mounting box at a height of 140 to 150 cm above the surface of the floor.

Mood control Niko Home Control. The mood setting display is used by the resident to select one of the pre-programmed mood settings. A mood setting is a combination of output settings with regard to lighting, roll-down shutters, sun blinds, etc. Mood settings are stored during the programming stage of the installation. The software includes 20 pictograms of which a maximum of eight pictograms can be selected. One or more actions are then linked to each one of those eight pictograms to help create the ideal mood for each occasion. Push buttons with display are integrated in a bridge. The flush-mounting frame is made from 1 mm-thick metal which is galvanized on all sides after cutting, even on the cut edges. On the horizontal and vertical axes, the flush-mounting frame has 4 grooves for screw mounting in flush-mounting boxes. These grooves have a screw aperture of 7 mm. For mounting on panels, the flush-mounting frame is equipped with 4 screw holes (indicated by a screw symbol) with a diameter of 3 mm. The middle of the flush-mounting frame is indicated (chalk line, laser, ..) in both the horizontal and vertical directions, so that mounting one or more mechanisms can be carried out quickly and easily. The flush-mounting frame is equipped, both on the top and the bottom, with a dark grey, plastic end border. This border is made of PC+ASA and is joined to the flush-mounting frame using a melting process. The corners of the two end borders are equipped with rectangular openings (7.9 x 1.5 mm) each containing a multi-positional snap hook. Thanks to the snap hooks, the 4 rectangular openings ensure that the flush surround plate can always be attached flat to the wall, even in cases of untidy plasterwork. This works in two directions: If the flush-mounting box sticks out of the plasterwork, the multi-positional snap hooks can compensate for a 1 to 1.2 mm margin; if the flush-mounting box is sunk too deeply in the plasterwork, the snap hooks can compensate for up to a 1.8 mm margin. The end borders also have 4 round openings that ensure the correct positioning of the flush surround plate in relation to the central plate. At the right and left sides, the flush-mounting frame is equipped with folded-up dovetails, allowing for a quick and perfect horizontal coupling of several switches. The folded-up edges on the outside of the base and their continuation to the inside ensure additional robustness. The bases can be coupled vertically with a centre-to-centre distance of 60 x 71 mm by sliding them into each other. They automatically lock into place. For horizontal coupling of bases with a centre-to-centre distance of 71 mm, the base is equipped with two pre-formed lips at the bottom. By folding these lips down over a length of 1 mm, this rests perfectly on the one below and the centre-to-centre distance of 71 mm is guaranteed. When mounting in a flush-mounting box with grip surfaces, use claws that can be rotated open using screws with a slotted screwhead (slot 0.8 x 5 mm). The claws, which have a depth of engagement of 31 mm, turn back completely when loosened.

- Flush-mounting depth: 20 mm
- Screen type: lit colour display with the dimensions 45 x 45 x 32 (HxWxD)
- Minimum ambient temperature: 0 °C
- Maximum ambient temperature: +50 °C
- Input voltage: 26 Vdc (SELV, safety extra-low voltage)
- Marking: CE



550-13041

4 year warranty

Mood control Niko Home Control



This control is connected directly to the installation and is used to set and call up a desired mood. Moods can also be automatically called up using sensors. This control is mounted in a flush-mounting box at a height of 140 to 150 cm above the surface of the floor.

Mood control Niko Home Control. The mood setting display is used by the resident to select one of the pre-programmed mood settings. A mood setting is a combination of output settings with regard to lighting, roll-down shutters, sun blinds, etc. Mood settings are stored during the programming stage of the installation. The software includes 20 pictograms of which a maximum of eight pictograms can be selected. One or more actions are then linked to each one of those eight pictograms to help create the ideal mood for each occasion. Push buttons with display are integrated in a bridge. The flush-mounting frame is made from 1 mm-thick metal which is galvanized on all sides after cutting, even on the cut edges. On the horizontal and vertical axes, the flush-mounting frame has 4 grooves for screw mounting in flush-mounting boxes. These grooves have a screw aperture of 7 mm. For mounting on panels, the flush-mounting frame is equipped with 4 screw holes (indicated by a screw symbol) with a diameter of 3 mm. The middle of the flush-mounting frame is indicated (chalk line, laser, ..) in both the horizontal and vertical directions, so that mounting one or more mechanisms can be carried out quickly and easily. The flush-mounting frame is equipped, both on the top and the bottom, with a dark grey, plastic end border. This border is made of PC+ASA and is joined to the flush-mounting frame using a melting process. The corners of the two end borders are equipped with rectangular openings (7.9 x 1.5 mm) each containing a multi-positional snap hook. Thanks to the snap hooks, the 4 rectangular openings ensure that the flush surround plate can always be attached flat to the wall, even in cases of untidy plasterwork. This works in two directions: If the flush-mounting box sticks out of the plasterwork, the multi-positional snap hooks can compensate for a 1 to 1.2 mm margin; if the flush-mounting box is sunk too deeply in the plasterwork, the snap hooks can compensate for up to a 1.8 mm margin. The end borders also have 4 round openings that ensure the correct positioning of the flush surround plate in relation to the central plate. The base is equipped on all sides with folded-up dovetails, allowing for both vertical and horizontal coupling (centre-to-centre distance of 71 x 71 mm) of several bases to be carried out quickly and perfectly. The folded-up edges on the outside of the base and their continuation to the inside ensure additional robustness. When fixing in a flush-mounting box screws should be used.

- Flush-mounting depth: 20 mm
- Screen type: lit colour display with the dimensions 45 x 45 x 32 (HxWxD)
- Minimum ambient temperature: 0 °C
- Maximum ambient temperature: +50 °C
- Input voltage: 26 Vdc (SELV, safety extra-low voltage)
- Dimensions (HxWxD): 73.1 mm
- Marking: CE



550-13042

4 year warranty

Mood control Niko Home Control



This control is connected directly to the installation and is used to set and call up a desired mood. Moods can also be automatically called up using sensors. This control is mounted in a flush-mounting box at a height of 140 to 150 cm above the surface of the floor.

Mood control Niko Home Control. The mood setting display is used by the resident to select one of the pre-programmed mood settings. A mood setting is a combination of output settings with regard to lighting, roll-down shutters, sun blinds, etc. Mood settings are stored during the programming stage of the installation. The software includes 20 pictograms of which a maximum of eight pictograms can be selected. One or more actions are then linked to each one of those eight pictograms to help create the ideal mood for each occasion. Push buttons with display are integrated in a bridge. The flush-mounting frame is made from 1 mm-thick metal which is galvanized on all sides after cutting, even on the cut edges. On the horizontal and vertical axes, the flush-mounting frame has 4 grooves for screw mounting in flush-mounting boxes. These grooves have a screw aperture of 7 mm. For mounting on panels, the flush-mounting frame is equipped with 4 screw holes (indicated by a screw symbol) with a diameter of 3 mm. The middle of the flush-mounting frame is indicated (chalk line, laser, ..) in both the horizontal and vertical directions, so that mounting one or more mechanisms can be carried out quickly and easily. The flush-mounting frame is equipped, both on the top and the bottom, with a dark grey, plastic end border. This border is made of PC+ASA and is joined to the flush-mounting frame using a melting process. The corners of the two end borders are equipped with rectangular openings (7.9 x 1.5 mm) each containing a multi-positional snap hook. Thanks to the snap hooks, the 4 rectangular openings ensure that the flush surround plate can always be attached flat to the wall, even in cases of untidy plasterwork. This works in two directions: If the flush-mounting box sticks out of the plasterwork, the multi-positional snap hooks can compensate for a 1 to 1.2 mm margin; if the flush-mounting box is sunk too deeply in the plasterwork, the snap hooks can compensate for up to a 1.8 mm margin. The end borders also have 4 round openings that ensure the correct positioning of the flush surround plate in relation to the central plate. At the right and left sides, the flush-mounting frame is equipped with folded-up dovetails, allowing for a quick and perfect horizontal coupling of several switches. The folded-up edges on the outside of the base and their continuation to the inside ensure additional robustness. The bases can be coupled vertically with a centre-to-centre distance of 60 x 71 mm by sliding them into each other. They automatically lock into place. For horizontal coupling of bases with a centre-to-centre distance of 71 mm, the base is equipped with two pre-formed lips at the bottom. By folding these lips down over a length of 1 mm, this rests perfectly on the one below and the centre-to-centre distance of 71 mm is guaranteed. When fixing in a flush-mounting box screws should be used.

- Flush-mounting depth: 20 mm
- Screen type: lit colour display with the dimensions 45 x 45 x 32 (HxWxD)
- Minimum ambient temperature: 0 °C
- Maximum ambient temperature: +50 °C
- Input voltage: 26 Vdc (SELV, safety extra-low voltage)
- Marking: CE

