

Fourfold faceplate, 71 mm centre distance, Niko Pure liquid black

242-76400

4 year
warranty

Fourfold faceplate with 71 mm centre-to-centre distance from the range Niko Pure. Niko Pure liquid black

Technical data

Fourfold faceplate, 71 mm centre distance, Niko Pure liquid black.

- Fourfold faceplate for four switches.
- Colour: enamelled liquid black (approximately NCS S 9000 N, RAL 9005)
- Frame composition: It consists of an upper frame and lower frame that are mechanically interconnected.
- Material upper frame: The upper frame is made of hard-coated PMMA.
- Material lower frame: The lower frame is made of dark grey polycarbonate (PC) + acrylic-styrene-acrylate (ASA), black coated.
- Frame thickness: The upper frame is 2 mm thick and the lower frame 6 mm.
- Centre-to-centre distance: 71 mm
- Surface-mounting height: max. 8.5 mm
- Fire safety
 - completely self-extinguishing faceplate
 - complies with a filament test of 650 °C
- Protection degree: IP41 for the combination of a mechanism, central plate and faceplate
- Impact resistance: The combination of a mechanism, a central plate and a faceplate has an impact resistance of IK06
- Dimensions (HxWxD): 83 x 296 x 8.9 mm
- Certification marks: CEBEC, KEMA, NF, VDE, ÖVE, SEMKO
- Marking: CE

