

Twilight switch, 24 V, 2-200 lux, IP54

350-10032

4 year
warranty

This twilight switch is used to switch the outdoor lighting and can be mounted on a wall. Thanks to the large sensor surface area, this device ensures a very accurate light measurement. You can adjust the light sensitivity yourself.

Finishing colour: white

- Sustainable
- Functional
- Reliable
- Greater comfort
- Improved burglary protection
- Can be combined with Niko Home Control

Automatic twilight switch for use in driveways, carports, gardens, etc.

- The twilight switch is suitable for controlling outdoor lighting.
- The lighting turns on automatically when the level of daylight drops below the programmed lux value. The lighting turns off automatically when the level of daylight is above the programmed lux value.
- The housing offers enough room for the cabling and thus allows quick, easy installation.
- Connection possible to Niko Home Control via the potential-free digital sensor module (550-00210).



24V



surface
mounting

niko

350-10032 - 16-04-2025

Technical data

Article number	350-10032
Input voltage	24 Vac/Vdc \pm 10 %
Detector output	24 V (ON/OFF)
Relay contact	N.O. (max. 4 A), potential-free
Light intensity range	2 lux – 200 lux
Number of channels	1 channel
Ambient temperature	-50 – +50 °C
Mounting method	surface mounting
Dimensions (HxWxD)	103 x 73 x 47 mm
Protection degree	IP54
Marking	CE

Dimensions



Wiring diagram

