

Presence or absence detector 360°, 30 m, KNX, 3 PIR elements, flush-mounting, square

351-25037

4 year warranty

The presence or absence detector with two channels and daylight control for flush mounting in ceilings is suitable for switching the indoor lighting on and off. The detector is equipped with an integrated light sensor and is only compatible with KNX.


- Combination of master/secondary possible
- Can be placed at a height of up to 8 metres




Presence detector for use in large rooms such as large offices and meeting rooms

- Everything can be programmed using ETS software
- Very simple programming
- Can be programmed as a presence or absence detector
- 2 channels for setting by heliometer
 - 1 channel for turning the lighting on and off
 - 1 channel for turning the HVAC installation on and off



Detection range



| D |  |  |  |
|-----|---------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
| 2 m | 5 m | 10 m | 20 m |
| 3 m | 7 m | 13 m | 26 m |
| 4 m | 9 m | 14 m | 28 m |
| 5 m | 10 m | 15 m | 30 m |
| 6 m | 10 m | 15 m | 30 m |
| 7 m | 10 m | 15 m | 30 m |
| 8 m | 10 m | 15 m | 30 m |



KNX



master



360 °



max.
26 m from
3 m height



2 – 8 m



flush-
mounting

niko

Technical data

| | |
|----------------------------|---------------------------|
| Article number | 351-25037 |
| Configuration | master |
| Input voltage | 24 Vdc \pm 10 % |
| Detector output | KNX |
| Light intensity range | 5 lux – 2000 lux |
| Number of channels | 2 channels |
| Detection angle | 360 ° |
| Detection range (PIR) | max. 26 m from 3 m height |
| Ambient temperature | -20 – +40 °C |
| Mounting method | flush-mounting |
| Mounting height | 2 – 8 m |
| Dimensions visible (HxWxD) | 42 mm |
| Dimensions (HxWxD) | 88 x 88 x 57 mm |
| Protection degree | IP20 |
| Marking | CE |

Accessories

Error applying XSLT stylesheet, check console for errors

Dimensions

