

Compact intercom for surface mounting with extension

This intercom for surface mounting consists of a basic module and an extension module. The extension module is provided with ten free function keys with an indication LED and a text field for personalisation. One of the following functionalities can be assigned to a free function key:


- communicating with an external audio unit and switching the door opener relay
- internal call
- call forwarding
- control function



10-512

4 year
warranty

Compact intercom for surface-mounting with extension, white



This device consists of a compact surface-mounting telephone 10-511 and an expansion module. The expansion module has 10 free function keys with feedback LEDs and a name plate. You can assign one of the following functions to the free function keys: communication with an external unit and switching of the door opener relay, internal call, contact-status indication of the bus indicator module (10-840), (de)activation of call diversion or transmission of a control function.

Compact intercom for surface-mounting with extension, white. surface-mounting / table-mounting (using a stand for table mounting)

- 2-way conversations
 - housing made of anti-static and recyclable plastic
 - blue door opener key with possibility to set a floor level door opening function
 - button to switch the lighting on/off
 - 1 control button: equipped with a control function / possibility to set a function of your choice: internal call, automatic door opener, call diversion.
 - 10 control buttons on the extension: equipped with control function / possibility to set a function of your choice: internal call, call from external unit, open door, call diversion, display of sensor status with binary input, variable control function (on / off)
 - a selection of 13 different ring tones
 - acoustic and visual call differentiation between apartment door, front door and internal call
 - acoustic call differentiation for 2 doors
 - volume can be set manually
 - visual display when the ringtone is switched off
 - possibility for 1 parallel call
 - visual display of a call (brief) via green LED
 - busy line displayed in the case of an existing connection
 - block listen in and automatic call termination
 - audio and video internal units can be combined in one system.
-
- Wiring technique: 3-wire technology required
 - Input current at rest: $I(a) = 0.5 \text{ mA}$, $I(P) = 20 \text{ mA}$ in standby
 - Maximum input current: $I(P_{max}) = 90 \text{ mA}$
 - Minimum ambient temperature: 0°C
 - Maximum ambient temperature: $+40^\circ\text{C}$
 - Finishing colour: white
 - Material upperframe: ABS

