

# Twofold faceplate, horizontal 71 mm centre distance, for a socket outlet and one 45x45 function, Niko Rocker and Niko Toggle steel champagne coated

166-74802

4 year warranty

The Niko Rocker and Niko Toggle twofold horizontally oriented faceplate clicks onto a socket outlet and one 45 x 45 mm function that have been horizontally installed next to each other with a centre distance of 71 mm. The faceplate combines with any available Niko Rocker and Niko Toggle socket outlet finishing set and a Niko 45 x 45 mm function. It consists of an upper frame, light guide and lower frame that are mechanically interconnected. The upper frame is made of steel. The lower frame is made of white polycarbonate (PC) + acrylic-styrene-acrylate (ASA), champagne coated. The upper frame is 2 mm thick and the lower frame 6 mm.

Niko recommends a design combination with a finishing set in the following colour: steel champagne coated for Niko Rocker and Niko Toggle finishing sets and champagne coated for other finishing sets.



- Exclusive materials
- Authentic vintage design
- Belgian design & craftsmanship
- Design matches Niko Pure portfolio
- Proven Niko quality
- Designed to fit the standard socket outlet base
- Designed to fit any available 45 x 45 mm function

## Technical data

Twofold faceplate, horizontal 71 mm centre distance, for a socket outlet and one 45x45 function, Niko Rocker and Niko Toggle steel champagne coated.

- Colour: enamelled champagne (approximately NCS S 4005 - Y20R, RAL 080 70 10)
- Recommended colour central plate: steel champagne coated for Niko Rocker and Niko Toggle finishing sets and champagne coated for other finishing sets
- Frame composition: It consists of an upper frame, light guide and lower frame that are mechanically interconnected.
- Material upper frame: The upper frame is made of steel.
- Material lower frame: The lower frame is made of white polycarbonate (PC) + acrylic-styrene-acrylate (ASA), champagne coated.
- Varnish upper frame: The upper frame is enamelled champagne.
- Varnish lower frame: The lower frame is enamelled champagne.
- Frame thickness: The upper frame is 2 mm thick and the lower frame 6 mm.
- Centre-to-centre distance: 71 mm
- Impact resistance: The combination of a mechanism, a central plate and a faceplate has an impact-resistance of IK06
- Dimensions (HxWxD): 83 x 154 x 13 mm
- Dimensions visible (HxWxD): 83 x 154 mm
- Certification marks: CEBEC, NF

**niko**

• Marking: CE



[www.niko.eu](http://www.niko.eu)

**niko**

16-74802 - 24-04-2025