

# Ventilation control with LED for Niko Home Control, champagne coated

157-52054

4 year  
warranty

This push button allows four ventilation positions to be set. It is attached to the wall-mounted printed circuit using a click mechanism. An LED indicates to which level the ventilation is set. Switch including button.  
Finishing colour: champagne coated.

## Technical data

Ventilation control with LED for Niko Home Control, champagne coated.

- Material central plate: The central plate is enamelled and made of rigid PC and ASA.
- Print: On the key in the bottom right corner a clock is printed to indicate the boost function. The three other keys are printed with a ventilator with the speed going anti-clockwise, starting with the key in the top left corner.
- Lens: The upper and lower keys are fitted at the bottom with a small amber-coloured indication LED (1.5 x 1.5 mm) to indicate the status of the action. Using the programming software, you can program the LEDs to light up when the output is either activated or deactivated .
- Colour: enamelled champagne (approximately NCS S 4005 - Y20R, RAL 080 70 10)
- Fire safety
  - the plastic parts of the central plate are self-extinguishing (comply with a filament test of 650 °C)
  - the plastic parts of the central plate are halogen-free
- Input voltage: 26 Vdc (SELV, safety extra-low voltage)
- Dismantling: To dismount simply pull the central plate off the base.
- Impact resistance: After mounting, an impact-resistance of IK06 is guaranteed.
- Dimensions (HxWxD): 44.5 x 44.5 x 8.6 mm
- Marking: CE

