


# Presence detector, 360°, 230 V, 12 m, slave, for surface mounting

**350-602021**

This flat and discrete presence detector is a slave detector that extends the detection range of a 230 V master detector. The detector is designed for surface mounting and has an IP54 protection degree. The detector's settings can be modified using the Niko detector tool app and 2-way Bluetooth® communication between a smartphone or tablet and the detector.

- Surface mounting
- Quick cabling using screwless and easily accessible plug-in terminals
- User-friendly app for settings (iOS/Android)
- 2-way Bluetooth® communication ensures quick modification of settings and live feedback in the app
- Pre-configured function:
  - adjustable PIR sensitivity (4 levels)
  - event log keeps track of recent changes
- Wireless communication between master- and slave detectors
- Settings and configuration can be locked with a PIN code
- IP54 protection degree



 **Bluetooth®**



230 V



slave



360°






2 – 3.5 m



12 m from  
a height of  
3 m



surface-mounting


			
2 m	3,2 m	4 m	8 m
2,5 m	4 m	5 m	10 m
3 m	4,8 m	6 m	12 m
3,5 m	5,6 m	7 m	14 m

## Technical data

**4** year  
warranty

Article number	350-602021
Configuration	slave
Input voltage	230 Vac $\pm$ 10 %, 50 Hz
Maximum power consumption	0.3 W
Detection angle	360 °
Detection range (PIR)	up to 12 m in diameter from a height of 3 m
Ambient temperature	-25 – 50 °C
Mounting method	surface mounting
Mounting height	2 – 3.5 m
Colour	white (RAL 9010)
Dimensions visible (HxWxD)	100 x 100 x 50 mm
Dimensions (HxWxD)	100 x 100 x 50 mm
Wire capacity	2.5 mm <sup>2</sup>
Maximum range Bluetooth®	25 m
Maximum radio frequency power	-5 dBm
Minimum distance between Bluetooth® devices	1.2 m
Protection degree	IP54
Impact resistance	IK02
Detector settings	Niko detector tool app and 2-way Bluetooth® communication
Marking	CE

## Dimensions



## Wiring diagram

