## Finishing set with 3 cinch audio connections, also for flush mounting in trunking systems, White

100-69717



Finishing set with three cinch audio connections. cream

## **Technical data**

Finishing set with 3 cinch audio connections, also for flush mounting in trunking systems, White.

- Function: The central plate is clicked into a 45 x 45 mm flush-mounting frame and must always be mounted with the 'TOP arrow' (indelibly imprinted on the rear of the central plate) pointing upwards. The central plate is equipped with a white, a red and a yellow cinch connector which are connected along the rear with three connector blocks.
- Material central plate: The central plate is made of rigid PC and ASA. The base material is coloured in mass.
- Colour: cream (coloured in mass, approximately RAL 1013)
- Fire safety
  - The plastic parts of the central plate are self-extinguishing (comply with a filament test of 650°C)
  - The plastic parts of the central plate are halogen-free.
- Wire connection
  - each connector block is equipped with cage clamps with permanent screws with a slotted screwhead (slot  $0.6 \times 3.5$  mm)
  - $\ \text{every screw is provided with a screwdriver slot that prevents the screwdriver from sliding off the screwhead}.$
- Dismantling: To dismount simply pull the central plate off the base.
- Protection degree: IP41 for the combination of a mechanism, central plate and faceplate
- Impact resistance: The combination of a mechanism, a central plate and a faceplate has an impact-resistance of IK06
- Dimensions (HxWxD): 44.7 x 44.7 x 8.6 mm
- Marking: CE





