Twofold faceplate with 71 mm centre distance, Niko Pure alu gold brushed

221-76800

Twofold faceplate with 71 mm centre distance from the range Niko Pure. Niko Pure alu gold brushed

Technical data

Twofold faceplate with 71 mm centre distance, Niko Pure alu gold brushed.

- Double faceplate for two switches.
- Colour: alu gold (approximately NCS S 3020 Y, RAL 1000)
- Frame composition: It consists of an upper frame and lower frame that are mechanically interconnected.
- Material upper frame: The upper frame is made of anodised brushed aluminium (alu gold).
- Material lower frame: The lower frame is made of white polycarbonate (PC) + acrylic-styrene-acrylate (ASA).
- Frame thickness: The upper frame is 2 mm thick and the lower fame 6 mm.
- Centre-to-centre distance: 71 mm
- Surface-mounting height: max. 8.5 mm
- Fire safety
 - self-extinguishing: complies with a filament test of 650°C
 - halogen-free
- Protection degree: IP41 for the combination of a mechanism, central plate and faceplate
- Impact resistance: The combination of a mechanism, a central plate and a faceplate has an impact-resistance of IK06
- Dimensions (HxWxD): 83 x 154 x 8.9 mm
- Dimensions visible (HxWxD): 83 mm
- Certification marks: CEBEC, KEMA, ÖVE, SEMKO, NF
- Marking: CE

CE



4 year warranty



221-76800 - 05-07-20

www.niko.eu