

Twofold faceplate, vertical 60 mm centre distance, for a double switch and a socket outlet function, Niko Rocker steel white coated

154-56258

4 year warranty


The Niko Rocker twofold vertically oriented faceplate clicks onto a double switch and a socket outlet function that have been vertically installed on top of each other with a centre distance of 60 mm. The faceplate combines with any available Niko Rocker set for double switch function and Niko Rocker and Niko Toggle socket outlet finishing set. It consists of an upper frame, light guide and lower frame that are mechanically interconnected. The upper frame is made of steel. The lower frame is made of white polycarbonate (PC) + acrylic-styrene-acrylate (ASA), white coated. The upper frame is 2 mm thick and the lower frame 6 mm. Niko recommends a design combination with a finishing set in the following colour: steel white coated for Niko Rocker and Niko Toggle finishing sets and white coated for other finishing sets.

- Exclusive materials
- Authentic vintage design
- Belgian design & craftsmanship
- Design matches Niko Pure portfolio
- Proven Niko quality
- Unique illuminated switch design (by adding feedback LED)
- Designed to fit the standard socket outlet base

Technical data

Twofold faceplate, vertical 60 mm centre distance, for a double switch and a socket outlet function, Niko Rocker steel white coated.

- Double faceplate for two switches.
- Colour: enamelled steel white (approximately NCS S 1002 - B50G, RAL 000 90 00)
- Recommended colour central plate: steel white coated for Niko Rocker and Niko Toggle finishing sets and white coated for other finishing sets
- Frame composition: It consists of an upper frame, light guide and lower frame that are mechanically interconnected.
- Material upper frame: The upper frame is made of steel.
- Material lower frame: The lower frame is made of white polycarbonate (PC) + acrylic-styrene-acrylate (ASA), white coated.
- Varnish upper frame: The upper frame is enamelled white.
- Frame thickness: The upper frame is 2 mm thick and the lower frame 6 mm.
- Centre-to-centre distance: 60 mm
- Impact resistance: The combination of a mechanism, a central plate and a faceplate has an impact resistance of IK06
- Dimensions (HxWxD): 143 x 83 x 13 mm
- Dimensions visible (HxWxD): 143 x 83 mm
- Certification marks: CEBEC, NF
- Marking: CE



niko

CE

www.niko.eu

niko

154-56258 - 02-07-2025