

Wireless switch with four buttons


This wireless switch with four buttons can be used by a smart switch or a wireless receiver. It can be used as a two dual-button controls (upper: on, lower off) or as four one-button controls (toggle on/off or pulse). The switch can also be used in the Niko Home Control installation in combination with the Niko Home Control RF interface Easywave.



410-00002

4 year warranty

Base for wireless switch with 4 control buttons



With this wireless switch, you control a maximum of 4 circuits, independent of one another, but dependent on the receiver settings. You use the switch for 1-key, 2-key and 4-key functions.

Technical characteristics:

- power supply voltage: battery, 3 V DC (supplied);
- transmission range: max. 30 meters indoors, 100 meters in open spaces;
- mounting: with the adhesive strips or screws provided.
- frequency band: 868,0 – 868,6MHz
- maximum power output: -3,25 dBm

Base for wireless switch with 4 control buttons. Wall-mounted transmitter with 4 connections with RF technology for wireless remote control of Niko RF receivers on the frequency 868.3MHz. Each transmitter can control an unlimited number of receivers. Each receiver can be controlled by a maximum of 32 transmitters. Maximum transmission range in a building: 30 m; in open spaces: 100 m. Modulation type: FSK. Supplied complete with battery and pre-programmed transmitter address. Buttons and faceplates are to be ordered separately. Battery type: Renata 3 V/270 mAh CR2430; Saft 3 V/270 mAh LM2430; Varta 3 V/260 mAh CR2430; Panasonic 3 V/250 mAh CR2330. Can be either stuck or screwed to the wall or flush-mounting box. In compliance with Belgian and European legislation: CE marking on the device. This product complies with all of the relevant European guidelines and regulations. For radio equipment, Niko nv declares that it is in compliance with Directive 2014/53 / EU. Can be used in all European Member States. User manual is included with the registration.

- Dimensions (HxWxD): 71 x 103 mm
- Marking: CE

