

Motion detector for hallways, 360°, 230 V, 1 channel, 32 m, for flush mounting

351-25005

4 year warranty

The motion detector with one channel for flush mounting in ceilings is suitable for switching indoor lighting on and off. You can always activate the light with a N.O. push button (230 Vac) (to be ordered separately). The detector is equipped with an integrated light sensor.

Technical data

Motion detector for hallways, 360°, 230 V, 1 channel, 32 m, for flush mounting.

- Detector technology: PIR
- Input voltage: 230 Vac \pm 10 %, 50 Hz
- Detector output: 230 V (ON/OFF)
- Number of channels: 1 channel
- Light intensity range: 5 lux – 2000 lux
- Switch-off delay: 10 s – 20 min
- Detection angle: 360°
- Detection range (PIR): \varnothing 32 m from a height of 8 m
- Ambient temperature: -20 – +40 °C
- Mounting method: flush-mounting
- Drill diameter: 48 mm
- Mounting height: 2 – 8 m
- Usage: for indoor use only
- Maximum load incandescent and halogen lamps ($\cos \phi = 1$): 2300 W
- Maximum load low voltage halogen lamps: 1150 W
- Maximum load economy lamps (CFLi): 350 W
- Maximum load LED lamps 230 V: 350 W
- Dimensions (HxWxD): 105 x 105 x 71 mm
- Dimensions visible (HxWxD): 35 x 105 x 105 mm
- Impact resistance: IK02
- Protection class: Class II device
- Marking: CE
- Detector technology: PIR
- Input voltage: 230 Vac \pm 10 %, 50 Hz
- Detector output: 230 V (ON/OFF)
- Number of channels: 1 channel
- Light intensity range: 5 lux – 2000 lux
- Switch-off delay: 10 s – 20 min
- Detection angle: 360°
- Detection range (PIR): \varnothing 32 m from a height of 8 m



niko

- Ambient temperature: -20 – +40 °C
- Mounting method: flush-mounting
- Drill diameter: 48 mm
- Mounting height: 2 – 8 m
- Usage: for indoor use only
- Maximum load incandescent and halogen lamps ($\cos = 1$): 2300 W
- Maximum load low voltage halogen lamps: 1150 W
- Maximum load economy lamps (CFLi): 350 W
- Maximum load LED lamps 230 V: 350 W
- Dimensions (HxWxD): 105 x 105 x 71 mm
- Impact resistance: IK02
- Protection class: Class II device
- Marking: CE

