

# Double socket outlet with side earthing and shutters, pre-wired, horizontal

- flush-mounting depth: 28.5 mm



16 A  
250 Vac

## Double socket outlet with side earthing and shutters, pre-wired, horizontal

- flush-mounting depth: 28.5 mm



16 A  
250 Vac

### BASE




**170-38800** Pieces: 5 With plug-in terminals, for screw fixing

### FINISHING SET



	<b>100-66901</b>	Pieces: 20		<b>101-66901</b>	Pieces: 20		<b>102-66901</b>	Pieces: 20
	<b>104-66901</b>	Pieces: 20		<b>121-66901</b>	Pieces: 10		<b>122-66901</b>	Pieces: 10
	<b>123-66901</b>	Pieces: 10		<b>124-66901</b>	Pieces: 10		<b>154-66901</b>	Pieces: 10
	<b>157-66901</b>	Pieces: 10		<b>161-66901</b>	Pieces: 10		<b>200-66901</b>	Pieces: 10
	<b>220-66901</b>	Pieces: 10		<b>221-66901</b>	Pieces: 10			

### COMPLETE UNIT WITH PLUG-IN TERMINALS, FOR SCREW FIXING




	<b>100-67940</b>	Pieces: 5		<b>101-67940</b>	Pieces: 5		<b>111-67940</b>	Pieces: 5
---	------------------	-----------	---	------------------	-----------	---	------------------	-----------

## 170-38800

4 year warranty

Base for double socket outlet with side earthing and shutters, flush-mounting depth 28.5 mm, plug-in terminals



Base for double, horizontal socket outlet with side earthing, screw fixing and shutters. This socket outlet has a flush-mounting depth of 28.5 mm. A finishing set and faceplate in the colour of your choice must be ordered separately.

Base for double socket outlet with side earthing and shutters, flush-mounting depth 28.5 mm, plug-in terminals. The sockets are equipped with plug-in terminals for clamping the wires. All connection terminals are located at the top of the end socket and can contain up to  $2 \times 2.5 \text{ mm}^2$  of wire. The stripping length (14 mm) of the wires is indelibly imprinted on the back of the base. On the horizontal axis, the grooves each have two screw holes of 7 mm so that the socket outlet can be easily mounted in a flush-mounting box. In this configuration, the screws are on the horizontal axis or in channelling systems with which the double, pre-wired socket outlet must be attached to the mounting brackets. By means of the screw holes, the flush-mounting frame is positioned over the screwheads of the screws of the flush-mounting box or mounting bracket and is then shifted to the desired position and screwed tight. For attachment to flush-mounting boxes where the screws are positioned on the vertical axis, the grooves are on the vertical axis, each one equipped with one screw hole. Thanks to the 7 mm screw holes, the flush-mounting frame is positioned over the screwheads of the screws of the flush-mounting box and is then shifted to the left in order to be attached in the correct position. The flush-mounting frame is made from 1 mm-thick metal which is galvanized on all sides after cutting, even on the cut edges. On the horizontal and vertical axes, the flush-mounting frame has 4 grooves for screw mounting in flush-mounting boxes. These grooves have a screw aperture of 7 mm. For mounting on panels, the flush-mounting frame is equipped with 4 screw holes (indicated by a screw symbol) with a diameter of 3 mm. The middle of the flush-mounting frame is indicated (chalk line, laser, ...) in both the horizontal and vertical directions, so that mounting one or more mechanisms can be carried out quickly and easily. The base is equipped on all sides with folded-up dovetails, allowing for both vertical and horizontal coupling (centre-to-centre distance of  $71 \times 71 \text{ mm}$ ) of several bases to be carried out quickly and perfectly. The folded-up edges on the outside of the base and their continuation to the inside ensure additional robustness. The 4 rectangular openings ( $7 \times 2.5 \text{ mm}$ ) in the flush-mounting frame can compensate for a margin of 1 to 1.2 mm if the flush-mounting box protrudes beyond the plasterwork. In the case of such a margin, the faceplate can still butt up perfectly against the wall.

- Protection degree: The combination of a mechanism, a central plate and a faceplate has a protection degree of IP20.
- Impact resistance: The combination of a mechanism, a central plate and a faceplate has an impact-resistance of IK06
- Flush-mounting depth: 28.5 mm
- Ambient temperature:  $-5 - +40 \text{ }^\circ\text{C}$
- Certification marks: ÖVE, KEMA, VDE
- Marking: CE

