

# Modular external audio unit for flush-mounting

## 4 modules: dome camera, audio, display and code lock

### Function description

This modular flush-mounted external unit offers an elegant and flexible solution for your projects (up to 256 housing units). The start screen of the display can be configured individually. The front plate is made from high-quality brushed stainless steel. This complete video set is equipped with a dome camera, audio, display and code lock module.

The dome camera module ensures excellent colour image quality, both during the day and at night. It makes it possible to activate a door call, have a conversation and open the door. Thanks to the 3 function keys on the display module, you can easily navigate through the alphabetically sorted resident list. You can also use the code lock module to navigate via the flat number.



### Technical data

Reference number	10-386
Dimensions	560 x 200 x 3 mm (HxWxD) (front plate) 540 x 180 x 50 mm (HxWxD) (flush-mounting frame)
Finishing colour, material	brushed steel; modules made of black aluminium
Vandal proof	yes
Input current in standby	I(a) = 0.4 mA, I(P) = 140 mA
Max. input current	I(Pmax) = 245 mA
Display	160 x 104 pixels (fully graphic, monochrome)
Wiring	6-wired
Extra terminals	yes (e.g. for connecting door opener)
Protection degree	IP44
Ambient temperature	-10 °C to +50 °C
Marking	CE marking
Max. number of housing units	256
Conversation mode	hands-free conversation (standard), full duplex conversation possible
Direct dialling	possible (in combination with 10-850)
Error detection and indication	yes
Memory	removable EEPROM memory
Configuration	Niko configuration software for access control

Dimensions

