Combination coax with RJ45 UTP Cat. 6A, PoE++ ready, Niko Invisible, white coated

154-10358

This combination coax with RJ45 in Niko Invisible design has an RJ45 UTP Cat. 6A ready connection and a coaxical connection. The RJ45 connection can be used to make a network connection with 2 devices for telephone, Ethernet, IP, PoE or internet applications. A PoE adapter is required to transport both data and power via the connector. A PoE adapter can be both a PoE injector or a PoE splitter.
A professional can customise the finishing set to coordinate with or blend into its surrounding surface for an ultra-minimalist look. It can be covered with any wallpaper and paint colour. And thanks to its enamelled finishing in the colour white coated, you can even use it without any covering.
Dedicated Niko Invisible installation kits are available for brickwork and plasterboard, as well as a hole saw that facilitates application in plasterboard surfaces.

- Minimalist architectural design
- Blends into the wall
- Only a signature circular outline is visible
- Niko quality
- One product combines power, data and tv
- RJ45 connectors approved for type 4 power

Technical data

Combination coax with RJ45 UTP Cat. 6A, PoE++ ready, Niko Invisible, white coated.
- TV frequency band: 2 GHz
- Service: 4PPoE
- PoE standard: IEEE 802.3BT Type 4
- Maximum power Component (at PD): 72 W
- Maximum power Source (at PSE): 100 W
- Voltage range (at PSE): 50.0-57.0 V
- Voltage range (at PD): 42.5-57 V
- Maximum current: 860 mA
- Pairs with current: 4
- Maximum cable resistance per pair set: 12.5 Ω
- Power management: Three power class levels negotiated by signature or 0.1 W steps negotiated by LLDP
- Derating of maximum cable ambient operating temperature: 10 °C (20 °F) with more than half of bundled cables at Imax
- Supported cabling: Category 5
- Supported modes: Mode A, Mode B, 4-pair mode
- Protection degree: IP41
- Dimensions (HxWxD): 75 x 75 x 38 mm
- Marking: CE

niko

$C\epsilon$

Dimensions

75 mm

70 mm

niko