

# Threefold faceplate, horizontal 71 mm centre distance, for two 45x45 functions and a double switch function, Niko Toggle alu gold brushed

227-57708

4 year warranty

The Niko Toggle threefold horizontally oriented faceplate clicks onto two 45 x 45 mm functions and two switch functions that have been horizontally installed next to each other with a centre distance of 71 mm. It consists of an upper frame, light guide and lower frame that are mechanically interconnected. The upper frame is made of anodised brushed aluminium (alu gold). The anodisation process may result in slight colour differences. The lower frame is made of white polycarbonate (PC) + acrylic-styrene-acrylate (ASA), gold coated. The upper frame is 6 mm thick and the lower frame 2 mm. Niko recommends a design combination with a finishing set in the following colour: alu gold for Niko Rocker and Niko Toggle finishing sets and gold coated for other finishing sets.



- Exclusive materials
- Authentic vintage design
- Belgian design & craftsmanship
- Design matches Niko Pure portfolio
- Proven Niko quality
- Unique illuminated switch design (by adding feedback LED)
- Designed to fit any available 45 x 45 mm function

## Technical data

Threefold faceplate, horizontal 71 mm centre distance, for two 45x45 functions and a double switch function, Niko Toggle alu gold brushed.

- Threefold faceplate for three switches.
- Colour: alu gold (approximately NCS S 3020 - Y, RAL 1000)
- Recommended colour central plate: alu gold for Niko Rocker and Niko Toggle finishing sets and gold coated for other finishing sets
- Frame composition: It consists of an upper frame, light guide and lower frame that are mechanically interconnected.
- Material upper frame: The upper frame is made of anodised brushed aluminium (alu gold). The anodisation process may result in slight colour differences.
- Material lower frame: The lower frame is made of white polycarbonate (PC) + acrylic-styrene-acrylate (ASA), gold coated.
- Varnish lower frame: The lower frame is enamelled gold.
- Frame thickness: The upper frame is 6 mm thick and the lower frame 2 mm.
- Lighting element
  - the faceplate is fitted with a light guide
  - the light guide is made of a translucent plastic
  - the light guide transports the light from the optional LED to the lever
  - please note that the faceplate should not be mounted upside down to ensure that the optional LED fits nicely with the light guide

**niko**

227-57708 - 27-04-2025

- Centre-to-centre distance: 71 mm
- Impact resistance: The combination of a mechanism, a central plate and a faceplate has an impact-resistance of IK06
- Dimensions (HxWxD): 83 x 225 x 13 mm
- Dimensions visible (HxWxD): 83 x 225 mm
- Marking: CE

