

Twofold faceplate with 71 mm centre distance, Niko Pure alu black brushed

224-76800

4 year
warranty

Twofold faceplate with 71 mm centre distance from the range Niko Pure. Niko Pure alu black brushed

Technical data

Twofold faceplate with 71 mm centre distance, Niko Pure alu black brushed.

- Double faceplate for two switches.
- Colour: alu black (approximately NCS S 8005 - R50B, RAL 000 20 00)
- Recommended colour central plate: alu black
- Frame composition: It consists of an upper frame and lower frame that are mechanically interconnected.
- Material upper frame: The upper frame is made of anodised brushed aluminium (alu black). The anodisation process may result in slight colour differences.
- Material lower frame: The lower frame is made of dark grey polycarbonate (PC) + acrylic-styrene-acrylate (ASA), black coated.
- Varnish lower frame: The lower frame is enamelled black.
- Frame thickness: The upper frame is 6 mm thick and the lower frame 2 mm.
- Centre-to-centre distance: 71 mm
- Surface-mounting height: max. 8.5 mm
- Fire safety
 - self-extinguishing: complies with a filament test of 650°C
 - halogen-free
- Protection degree: IP41 for the combination of a mechanism, central plate and faceplate
- Impact resistance: The combination of a mechanism, a central plate and a faceplate has an impact resistance of IK06
- Dimensions (HxWxD): 83 x 154 x 8.9 mm
- Dimensions visible (HxWxD): 83 x 154 x 8 mm
- Certification marks: CEBEC, SEMKO, VDE, NF, KEMA, ÖVE
- Marking: CE

