

Splashproof, illuminable double push button 10 A/250 Vac with 2 N.O. or N.C. contacts, with screw terminals, black

761-35100

4 year
warranty

This illuminable double push button is equipped with two keys and two normally open (N.O.) or normally closed (N.C) contacts. It is designed to be mounted in a splashproof mounting box. Underneath the mechanism, there are two recesses for integration of two lighting units with wires. The entire unit is splashproof which makes it extremely well-suited for use in damp areas and in ammonia-rich environments. The lighting units must be ordered separately. Colour combination: black.

Faster and easier installation:

- all connections terminals are located at the top of the base:
 - to ensure all wires can be cut and stripped at the same length
 - to guarantee more space under the mechanism, so you can easily fold the wires and place the mechanism in the box without the wiring pushing it back up.




Technical data

Splashproof, illuminable double push button 10 A/250 Vac with 2 N.O. or N.C. contacts, with screw terminals, black.

- Function: – push button
 - block-shaped silver contacts (cadmium-free) in the form of a cross
- Maximum MCB rating: 16 A (limited by national installation rules)
- Colour: The base material is mass-dyed, black (RAL 9005)
- Colour combination: black
- Sealing: The cover has an integral closure and is hermetically sealed onto the appropriate box.
- Lens: At the bottom middle, the two keys are fitted with a square transparent lens (6.7 x 6.7 mm) for switches and push buttons which can be equipped with two lighting units.
- Number of mechanisms: 1
- Material base
 - ureumformaldehyde (UF) with high heat resistance
 - white RAL9010 (approximately)
- Material finishing: The switch/push button is made of impact-resistant, dust-resistant, halogen-free and self-extinguishing polypropylene (UL94-V2/1.6 mm). The control button is made of rigid ABS.
- Wire connection
 - connection terminals with combination screwhead (Pz1-Slot 0.85 x 5 mm)
 - screwdriver slot prevents the screwdriver from sliding off the screwhead
- Cable space
 - 21.9 mm wiring space under the mechanism
 - mechanism is held by 2 laterally positioned holders in the box
 - a snap connector holds the wired mechanism in place
- Stripping length
 - 8 mm stripping length

niko

- indelibly indicated at the rear side: stripping length and wiring diagram
- indelibly indicated at the front side: terminals and switch symbol
- Lighting element
 - the base is provided with 2 rectangular recesses for lighting units
 - left and right recess: lighting units with wires can be clicked in
- Surface-mounting box: The function is designed to be mounted in a splashproof mounting box. The function has an integral closure and is hermetically sealed onto the appropriate box (to be ordered separately).
- Chemical resistance: tested and approved for use in environments with ammonia levels up to 20 ppm
- Ambient temperature: -25 – +55 °C
- Protection degree: IP55 for the combination of a function and a splashproof mounting box
- Impact resistance: The combination of a Hydro mechanism and a flush- or surface-mounting box has an impact resistance of IK07 with a minimum temperature of -25 °C and a maximum temperature of 55 °C
- Certification marks: CEBEC, DEMKO, VDE, ÖVE, SEMKO, KEMA
- Marking: CE



Wiring diagram

