


Presence detector, 360°, 230 V, 12 m, master, for surface mounting

350-602121

This presence detector is a 1 channel master detector for automatic lighting control. The detector is designed for surface mounting and has an IP54 protection degree. The detector's settings can be modified using the Niko detector tool app and 2-way Bluetooth® communication between a smartphone or tablet and the detector.

- Surface mounting
- Quick cabling using screwless and easily accessible plug-in terminals
- User-friendly app for commissioning (iOS/Android)
- 2-way Bluetooth® communication ensures quick modification of settings and live feedback in the app
- Pre-configured function:
 - adjustable PIR sensitivity (4 levels)
 - eventlog keeps track of recent changes
- Detection range can be increased using up to 10 slave detectors
- Wireless communication between master and slave detectors
- Robust potential-free relay
- Automatic lighting control can be overridden with a 230 V push button - different options available
- Settings and configuration can be locked with a PIN-code
- Cloud solution for backing up and exchanging configuration files
- IP54 protection degree



Bluetooth®



| | ↙ | ⤓ | ⤔↑ | ⤕⤖ |
|-------|-------|-----|------|----|
| 2 m | 3,2 m | 4 m | 8 m | |
| 2,5 m | 4 m | 5 m | 10 m | |
| 3 m | 4,8 m | 6 m | 12 m | |
| 3,5 m | 5,6 m | 7 m | 14 m | |

Technical data


4 year warranty

| | |
|--|---|
| Article number | 350-602121 |
| Configuration | master |
| Input voltage | 230 Vac $\pm 10\%$, 50 Hz |
| Maximum power consumption | 0.3 W |
| Relay contact 1 | NO (max. $\mu 10$ A), potential-free |
| Maximum load incandescent and halogen lamps ($\cos\phi=1$) | 2300 W |
| Maximum load fluorescent lamps ($\cos\phi \geq 0.5$) | 1200 VA |
| Maximum load economy lamps (CFLi) | 350 W |
| Maximum load LED lamps 230 V | 350 W |
| Maximum load LED driver | 500 VA |
| Maximum load electronic transformer | 500 VA |
| Maximum switching current | 165 A/20 ms – 800 A/200 μ s |
| Light intensity range | 20 lux – 2000 lux, ∞ |
| Number of channels | 1 channel |
| Switch-off delay | pulse, 15 s – 2 h, ∞ |
| Detection angle | 360 ° |
| Detection range (PIR) | up to 12 m in diameter from a height of 3 m |
| Ambient temperature | -25 – 50 °C |
| Mounting method | surface mounting |
| Mounting height | 2 – 3.5 m |
| Colour | white (RAL 9010) |
| Dimensions visible (HxWxD) | 100 x 100 x 50 mm |
| Dimensions (HxWxD) | 100 x 100 x 50 mm |
| Wire capacity | 2.5 mm ² |
| Maximum range Bluetooth® | 25 m |
| Maximum radio frequency power | -5 dBm |
| Minimum distance between Bluetooth® devices | 1.2 m |
| Protection degree | IP54 |
| Impact resistance | IK02 |
| Detector settings | Niko detector tool app and 2-way Bluetooth® communication |
| Marking | CE |

Accessories

350-602021 Presence detector, 360°, 230 V, 12 m, slave, for surface mounting

Dimensions



Wiring diagram

