Threefold faceplate, 71 mm centre distance, Niko Intense dark brown coated

124-76700



Threefold faceplate with 71 mm centre-to-centre distance from the range Niko Intense. Niko Intense dark brown coated

Technical data

Threefold faceplate, 71 mm centre distance, Niko Intense dark brown coated.



- Colour: enamelled dark brown (approximately NCS S 8505 Y20R, RAL 060 30 05)
- Frame composition: It consists of an upper frame and lower frame that are mechanically interconnected.
- Material upperframe: The upperframe is made from impact-resistant, dimensionally stable polycarbonate.
- \bullet Material lower frame: The lower frame is made of grey coated polycarbonate (PC) + acrylic-styrene-acrylate (ASA)
- Centre-to-centre distance: 71 mm
- Surface-mounting height: max. 8.5 mm
- Fire safety
 - self-extinguishing: complies with a filament test of 650°C
 - halogen-free
- Protection degree: IP41 for the combination of a mechanism, central plate and faceplate
- Impact resistance: The combination of a mechanism, a central plate and a faceplate has an impact-resistance of IKO6
- Dimensions (HxWxD): 85 x 225 x 8.9 mm
- Certification marks: CEBEC, KEMA, NF, VDE, ÖVE, SEMKO
- Marking: CE

ϵ

