

Double socket outlet with side earthing and shutters, vertical, white

101-67865

4 year warranty

Technical data

Double socket outlet with side earthing and shutters, vertical, white

- Colour: white (mass-dyed, approximately NCS S 0502 - Y50R, RAL 9010)
- Type of earthing: side earthing
- Power: 16 A/230 Vac
- Flush-mounting frame
 - 1 mm-thick metal
 - galvanized on all sides
 - with 2 grooves
- Material faceplate: The central plate is made of impact-resistant, dustproof and rigid polycarbonate. The base material is mass-dyed.
- Material earthing: side earthing in high quality brass
- Fixing method
 - with screws for simple fixing in a flush-mounting box with grip surfaces
- Wire connection
 - contact buses fitted with plug-in terminals for clamping the wires
- Wire capacity
 - 2 x 2.5 mm² per connection terminal
- Earthing wire capacity
 - 2 x 2.5 mm² + 2 x 4 mm² wire in the earthing terminal
- – All plastic components are self-extinguishing (comply with a filament test of 650°C) and are halogen-free.
- Impact resistance: After mounting, an impact-resistance of IK06 is guaranteed.
- Dimensions (HxWxD): 106.8 x 81 x 63 mm
- Certification marks: KEMA, DEMKO, VDE, SEMKO
- Marking: CE

$\frac{16}{250}$ A/Vac



niko

Wiring diagram

