

Threefold faceplate, horizontal 71 mm centre distance, for two double and a single switch function, Niko Rocker alu blue grey brushed

226-56704

4 year warranty

The Niko Rocker threefold horizontally oriented faceplate clicks onto two double and a single switch function that have been horizontally installed next to each other with a centre distance of 71 mm. The faceplate combines with any available Niko Rocker for single and double switch functions. It consists of an upper frame, light guide and lower frame that are mechanically interconnected. The upper frame is made of anodised brushed aluminium (alu blue grey). The anodisation process may result in slight colour differences. The lower frame is made of dark grey polycarbonate (PC) + acrylic-styrene-acrylate (ASA), blue grey coated. The upper frame is 6 mm thick and the lower frame 2 mm.

Niko recommends a design combination with a finishing set in the following colour: alu blue grey.



- Exclusive materials
- Authentic vintage design
- Belgian design & craftsmanship
- Design matches Niko Pure portfolio
- Proven Niko quality
- Unique illuminated switch design (by adding feedback LED)

Technical data

Threefold faceplate, horizontal 71 mm centre distance, for two double and a single switch function, Niko Rocker alu blue grey brushed.

- Threefold faceplate for three switches.
- Colour: alu black (approximately NCS S 8005 - R50B, RAL 000 20 00)
- Recommended colour central plate: alu blue grey
- Frame composition: It consists of an upper frame, light guide and lower frame that are mechanically interconnected.
- Material upper frame: The upper frame is made of anodised brushed aluminium (alu blue grey). The anodisation process may result in slight colour differences.
- Material lower frame: The lower frame is made of dark grey polycarbonate (PC) + acrylic-styrene-acrylate (ASA), blue grey coated
- Varnish lower frame: The lower frame is enamelled blue grey.
- Frame thickness: The upper frame is 6 mm thick and the lower frame 2 mm.
- Lighting element
 - the faceplate is fitted with a light guide
 - the light guide is made of a translucent plastic
 - the light guide transports the light from the optional LED to the lever
 - please note that the faceplate should not be mounted upside down to ensure that the optional LED fits nicely with the light guide
- Centre-to-centre distance: 71 mm
- Impact resistance: The combination of a mechanism, a central plate and a faceplate has an impact resistance

niko

226-56704 - 02-07-2025

of IK06

- Dimensions (HxWxD): 83 x 225 x 13 mm
- Dimensions visible (HxWxD): 83 x 225 mm
- Marking: CE

