## Threefold faceplate with 71 mm centre-to-centre distance Niko Pure natural soft grey

## 159-76700



Threefold faceplate with 71 mm centre-to-centre distance from the range Finishing colour faceplate: Niko Pure natural soft grey

## Technical data

Threefold faceplate with 71 mm centre-to-centre distance Niko Pure natural soft grey.



- Threefold faceplate for three switches.
- Colour: natural soft grey (approximately NCS S 2005 Y10R, RAL 090 80 10)
- Frame composition: It consists of an upper frame and lower frame that are mechanically interconnected.
- Material upperframe: The upperframe is made of marmoleum.
- Material underframe: The lower frame is made of dark grey pc + ASA.
- Frame thickness: The upper frame is 2 mm thick and the underframe 6 mm.
- Precautions: It is best not to place this faceplate in rooms that are continually damp (e.g. pools, saunas).
- Surface-mounting height: max. 8.5 mm
- Fire safety
  - the complete faceplate is halogen-free.
- Protection degree: IP41 for the combination of a mechanism, central plate and faceplate
- Impact resistance: The combination of a mechanism, a central plate and a faceplate has an impact-resistance of IK06
- Dimensions (HxWxD): 83 x 225 x 8.9 mm
- Certification marks: CEBEC, KEMA, NF, VDE, ÖVE, SEMKO
- Marking: CE

