

# double vertical flush-mounting frame

This double vertical flush-mounting frame is suitable for two functions. The entire unit is splashproof which makes it extremely well-suited for use in damp areas and in demanding environments.



## double vertical flush-mounting frame

This double vertical flush-mounting frame is suitable for two functions. The entire unit is splashproof which makes it extremely well-suited for use in damp areas and in demanding environments.



### DOUBLE VERTICAL FLUSH-MOUNTING FRAME



	<b>700-74000</b>	Pieces: 3	Grey
	<b>701-74000</b>	Pieces: 3	White
	<b>761-74000</b>	Pieces: 3	Black

### ACCESSORY



<b>170-00093</b>	Pieces: 100	Screw HI-LO 3.2 x 13 (to be ordered per 100 items)
------------------	-------------	--

## 700-74000

4 year  
warranty

### Double vertical frame, grey



This double vertical frame is suitable for flush mounting two Niko Hydro functions. The entire unit is splashproof which makes it particularly suitable for use in damp areas and in demanding environments. Finishing colour: grey

Double vertical frame, grey.

- Number of mechanisms: 2
- Protection degree: See protection degree of the mounted function
- Impact resistance: The combination of a Hydro mechanism and a flush- or surface-mounting box has an impact resistance of IK07 with a minimum temperature of -25 °C and a maximum temperature of 55 °C
- Colour: The base material is coloured in mass, light grey (RAL 7035 or NCS S1502-B).
- Certification marks: CEBEC, ÖVE, KEMA, NF
- Marking: CE



## 701-74000

4 year  
warranty

### Double vertical frame, white



This double vertical frame is suitable for flush mounting two Niko Hydro functions. The entire unit is splashproof which makes it particularly suitable for use in damp areas and in demanding environments. Finishing colour: white

Double vertical frame, white.

- Number of mechanisms: 2
- Protection degree: See protection degree of the mounted function
- Impact resistance: The combination of a Hydro mechanism and a flush- or surface-mounting box has an impact resistance of IK07 with a minimum temperature of -25 °C and a maximum temperature of 55 °C
- Colour: The base material is coloured in mass, white (RAL 9010).
- Certification marks: CEBEC, ÖVE, KEMA, NF
- Marking: CE



## 761-74000

4 year warranty

### Double vertical frame, black



This double vertical frame is suitable for flush mounting two Niko Hydro functions. The entire unit is splashproof which makes it particularly suitable for use in damp areas and in demanding environments. Finishing colour: black

Double vertical frame, black.

- Number of mechanisms: 2
- Protection degree: See protection degree of the mounted function
- Impact resistance: The combination of a Hydro mechanism and a flush- or surface-mounting box has an impact resistance of IK07 with a minimum temperature of -25 °C and a maximum temperature of 55 °C
- Colour: The base material is coloured in mass, black (RAL 9005).
- Certification marks: CEBEC, ÖVE, KEMA, NF
- Marking: CE

