


Connected switching socket outlet for Niko Home Control with pin earthing and shutters, Zigbee®, 16 A, plug-in terminals

170-33505

4 year warranty

With this connected switching socket outlet with built-in consumption measurement, you choose extra comfort, safety and energy awareness. The socket outlet can be easily installed in all new construction projects and can also easily replace an existing socket outlet in renovation projects without adapting the wiring.

You connect the socket outlet without additional cabling with a wireless switch and the wireless smart hub (552-00001) for Niko Home Control. That way you have full control over your socket outlets and can add useful new features such as an all-off or all-on function, automatic calendar functions, remote control, consumption messages and an overview of your energy consumption.



- One-on-one exchangeable with the classic socket without rewiring
- True 16 A and CEBEC and NF certified, keeps existing circuit breaker
- Switching and measuring in Niko Home Control eco system
- Up to 3 consumption levels can be set to trigger other Niko Home Control actions or notifications
- Local control button with feedback LED
- Compatible with all Niko mechanisms and finishings
- Screwless central cover plate for faster installation

Technical data

Connected switching socket outlet for Niko Home Control with pin earthing and shutters, Zigbee®, 16 A, plug-in terminals.

- Input voltage: 230 Vac \pm 10%, 50 Hz
- Wire capacity: 2 x 2,5 mm²
- Standby consumption: 0.15 W
- Maximum load: 16 A / 3680 W
- Internal overcurrent protection: switches off at > 16 A
- Internal overheating protection
- Not suitable for heavy loads that have long and cycling operations above 2300 W such as electric vehicle charging (in mode 1 or 2), electrical heating devices or heavy inductive loads (eg. motors). When controlling these loads the temperature protection mechanism may be activated
- Communication protocol: Zigbee® 3.0, 2.4 GHz
- Maximum frequency power: 10 dBm
- Button on the device to switch the phase (L) on and off locally
- LED indicator for status and error information
- Measuring precision (valid for a normal voltage - 230 Vac). This device should not be used for billing purposes. The data recorded by this device should be used for information purposes only:
 - \pm 0,5 W (in range 1 - 5 W)
 - \pm 5 % (in range 5 - 3680 W)
- System compatibility: Zigbee® 3.0, Niko Home Control II
- Modification of settings: Niko Home app or Niko Home Control programming software
- Maximum number per Niko Home Control installation: 25
- Circuit breaker (to be installed in accordance with the applicable regulations):
 - 2,5 mm² wiring: maximum MCB rating C20
 - 1,5 mm² wiring: maximum MCB rating C16
- Fire safety
 - All plastic components are self-extinguishing (comply with a filament test of 650°C) and are halogen-free.

- Protection degree: The combination of a mechanism, a central plate and a faceplate has a protection degree of IP20-D
- Impact resistance: The combination of a mechanism, a central plate and a faceplate has an impact resistance of IK02
- Material base
 - ureumformaldehyde (UF) with high heat resistance
 - white RAL9010 (approximately)
- Material earthing: solid brass nickel-plated pin earthing
- Flush-mounting frame
 - 1 mm-thick metal
 - galvanized on all sides after cutting, even on the cut edges
 - with 4 grooves with screw hole of 7 mm
 - with 4 screw holes (indicated by a screw symbol) with a diameter of 3 mm for mounting on panels
- Flush mounting depth: 32.4 mm
- Required type of flush-mounting box
 - depth: min. 45 mm (cabling space included)
 - claw/screw fixing: 60 mm
 - inner diameter box: 60 mm
 - multiple boxes centre distance horizontal: 71 mm
 - multiple boxes centre distance vertical: 71 mm
 - multiple boxes centre distance vertical: 60 mm for Belgium and France
- Fixing method
 - simple mounting in a flush-mounting box with grip surfaces
 - with claws that rotate open using screws with a combination screwhead (Pz2 or slot 1 x 5.5 mm), for mounting in a flush-mounting box with grip surfaces
 - engagement depth of claws: 23.5 mm
 - claws turn back completely when loosened
- Centre-to-centre distance
 - Simple and quick assembly of one or more mechanisms by the indication (chalk line, laser, etc.) of the centre of the flush-mounting frame
 - vertical coupling centre-to-centre distance 60 mm by sliding several bases into each other, they lock themselves automatically
 - vertical coupling centre-to-centre distance 71 mm using pre-formed lips at the bottom, by folding the lips downwards over a length of 1 mm, the bases support each other and the centre-to-centre distance is guaranteed.
 - horizontal connection of multiple bases is quick and perfect thanks to the folded-up dovetails on the left and right sides
 - extra robustness due to the folded-up edges on the outside of the base and the continuation into the inside of the base
- End border: 4 rectangular openings (7 x 2.5 mm) which, if the flush-mounting box protrudes from the plasterwork, can compensate for a margin of between 1 and 1.2 mm, so that the faceplate can still butt up perfectly against the wall
- Wire connection
 - contact buses fitted with plug-in terminals for clamping the wires
- Wire capacity
 - all connection terminals at the top side of the base
 - up to 2 x 2.5 mm² wire per terminal
- Stripping length
 - 10 – 12 mm stripping length
 - indelibly indicated near the terminals: stripping length, terminals and switch symbol
- Ambient temperature: 0 – +40 °C
- Dimensions (HxWxD): 71.5 x 73 x 37.6 mm
- Weight: 98 g
- Certification marks: CEBEC, NF
- Marking: CE



[illegible]

552-00001
wireless
smart hub

(max. 25)

The diagram shows a grey, cube-shaped wireless smart hub with the 'mimo' logo. It is connected via a cable to a 25-pin D-sub connector. The connector is labeled with 'N', a ground symbol, and 'L' above the pins. The pins are color-coded: blue for N, green for ground, and black for L. The connector is also labeled with 'N', a ground symbol, and 'L' to the left of the pins.