

# Detector 360°, 32 m, with 3 zone DALI daylight control and extra functionalities, secondary, for flush mounting in high ceilings, (white)

**350-41762**


**4** year warranty

This presence detector (DALI daylight control, secondary) is suitable for flush-mounting in ceilings with a height of 4 – 8 m and can only be used in combination with the master (350-41760) to increase its detection range. The device follows the settings of the master. The sensitivity of the secondary detector, though, can be set separately. A maximum of ten secondary detectors can be connected per master.

Finishing colour: white



## Detection range



DALI



secondary



360°



circle, 16 – 32 m



4 – 8 m



flush-mounting

4 m	9,6 m	16 m
5 m	12 m	20 m
6 m	14 m	24 m
7 m	16,8 m	28 m
8 m	19,2 m	32 m

## Technical data

Article number	350-41762
Input voltage	via the DALI bus
Detector output	DALI
Detection angle	360 °
Detection range (PIR)	circle, 16 – 32 m
Ambient temperature	-5 – +50 °C
Mounting method	flush-mounting
Mounting height	4 – 8 m
Drill diameter	88.5 mm
Dimensions visible (HxWxD)	464 mm
Dimensions (HxWxD)	100 x 100 x 136.4 mm
Wire capacity	1 x 2.5 mm <sup>2</sup>
Protection degree	IP54
Marking	CE

## Accessories

350-41936	Universal remote control for smartphone
350-41934	IR-remote control for users

## Dimensions

