

Adsl/VDSL splitter RJ11

Suitable for ADSL, ADSL2, ADSL2+ and VDSL2 (standard ITU G.933.2).



Adsl/VDSL splitter RJ11

Suitable for ADSL, ADSL2, ADSL2+ and VDSL2 (standard ITU G.933.2).



BASE



170-09090 Pieces: 10 With screw terminals and claw fixing



170-09091 Pieces: 10 With screw terminals and screw fixing




170-79090 Pieces: 10 With screw terminals and claw fixing, centre distance 71 mm

FINISHING SET



100-69091 Pieces: 10
104-69091 Pieces: 10
123-69091 Pieces: 10
157-69091 Pieces: 10
220-69091 Pieces: 10



101-69091 Pieces: 10
121-69091 Pieces: 10
124-69091 Pieces: 10
161-69091 Pieces: 10
221-69091 Pieces: 10



102-69091 Pieces: 10
122-69091 Pieces: 10
154-69091 Pieces: 10
200-69091 Pieces: 10

COMPLETE UNIT FOR CLAW FIXING



100-69090 Pieces: 10
101-69090 Pieces: 10

COMPLETE UNIT FOR SCREW FIXING, CENTRE DISTANCE 71 MM



100-79090 Pieces: 10
101-79090 Pieces: 10

DIN RAIL CONNECTOR (INCL. DIN RAIL ADAPTER AND CONNECTOR RJ11 UTP)




650-11113 Pieces: 10 DIN rail RJ11 UTP

170-09090

4 year warranty

Flush-mounting socket ADSL splitter, claw fixing



Flush-mounting socket with screw terminals and claws with RJ11 outlet and ADSL outlet, with claw fixing. This ADSL splitter can also be used for ADSL2, ADSL2+ and VDSL2.

Flush-mounting socket ADSL splitter, claw fixing. The stripping length is around 3 mm. When mounting the socket outlet in a flush-mounting box with grip surfaces, use claws that can be rotated open using screws with a combination screwhead (Pz1 or slot 1 x 5 mm). The claws, which have a depth of engagement of 31 mm, can be manually pushed back into their original position after unscrewing. These claws can also be easily pushed out using a screwdriver. The flush-mounting frame is made from 1 mm-thick metal which is galvanized on all sides after cutting, even on the cut edges. On the horizontal and vertical axes, the flush-mounting frame has 4 grooves for screw mounting in flush-mounting boxes. These grooves have a screw aperture of 7 mm. For mounting on panels, the flush-mounting frame is equipped with 4 screw holes (indicated by a screw symbol) with a diameter of 3 mm. The middle of the flush-mounting frame is indicated (chalk line, laser, ..) in both the horizontal and vertical directions, so that mounting one or more mechanisms can be carried out quickly and easily. At the right and left sides, the flush-mounting frame is equipped with folded-up dovetails, allowing for a quick and perfect horizontal coupling of several switches. The folded-up edges on the outside of the base and their continuation to the inside ensure additional robustness. The bases can be coupled vertically with a centre-to-centre distance of 60 x 71 mm by sliding them into each other. They automatically lock into place. For horizontal coupling of bases with a centre-to-centre distance of 71 mm, the base is equipped with two pre-formed lips at the bottom. By folding these lips down over a length of 1 mm, this rests perfectly on the one below and the centre-to-centre distance of 71 mm is guaranteed. The flush-mounting frame is equipped, both on the top and the bottom, with a dark grey, plastic end border. This border is made of PC+ASA and is joined to the flush-mounting frame using a melting process. The corners of the two end borders are equipped with rectangular openings (7.9 x 1.5 mm) each containing a multi-positional snap hook. Thanks to the snap hooks, the 4 rectangular openings ensure that the flush surround plate can always be attached flat to the wall, even in cases of untidy plasterwork. This works in two directions: If the flush-mounting box sticks out of the plasterwork, the multi-positional snap hooks can compensate for a 1 to 1.2 mm margin; if the flush-mounting box is sunk too deeply in the plasterwork, the snap hooks can compensate for up to a 1.8 mm margin. The end borders also have 4 round openings that ensure the correct positioning of the flush surround plate in relation to the central plate.

- Protection degree: The combination of a switch, a central plate and a flush surround plate has a protection degree of IP41.
- Marking: CE



170-09091

4 year warranty

Flush-mounting socket ADSL splitter, screw fixing



Flush-mounting socket with screw terminals and claws with RJ11 outlet and ADSL outlet, with screw fixing. This ADSL splitter can also be used for ADSL2, ADSL2+ and VDSL2.

Flush-mounting socket ADSL splitter, screw fixing. The stripping length is around 3 mm. When fixing in a flush-mounting box screws should be used. The flush-mounting frame is made from 1 mm-thick metal which is galvanized on all sides after cutting, even on the cut edges. On the horizontal and vertical axes, the flush-mounting frame has 4 grooves for screw mounting in flush-mounting boxes. These grooves have a screw aperture of 7 mm. For mounting on panels, the flush-mounting frame is equipped with 4 screw holes (indicated by a screw symbol) with a diameter of 3 mm. The middle of the flush-mounting frame is indicated (chalk line, laser, ..) in both the horizontal and vertical directions, so that mounting one or more mechanisms can be carried out quickly and easily. At the right and left sides, the flush-mounting frame is equipped with folded-up dovetails, allowing for a quick and perfect horizontal coupling of several switches. The folded-up edges on the outside of the base and their continuation to the inside ensure additional robustness. The bases can be coupled vertically with a centre-to-centre distance of 60 x 71 mm by sliding them into each other. They automatically lock into place. For horizontal coupling of bases with a centre-to-centre distance of 71 mm, the base is equipped with two pre-formed lips at the bottom. By folding these lips down over a length of 1 mm, this rests perfectly on the one below and the centre-to-centre distance of 71 mm is guaranteed. The flush-mounting frame is equipped, both on the top and the bottom, with a dark grey, plastic end border. This border is made of PC+ASA and is joined to the flush-mounting frame using a melting process. The corners of the two end borders are equipped with rectangular openings (7.9 x 1.5 mm) each containing a multi-positional snap hook. Thanks to the snap hooks, the 4 rectangular openings ensure that the flush surround plate can always be attached flat to the wall, even in cases of untidy plasterwork. This works in two directions: If the flush-mounting box sticks out of the plasterwork, the multi-positional snap hooks can compensate for a 1 to 1.2 mm margin; if the flush-mounting box is sunk too deeply in the plasterwork, the snap hooks can compensate for up to a 1.8 mm margin. The end borders also have 4 round openings that ensure the correct positioning of the flush surround plate in relation to the central plate.

- Protection degree: The combination of a switch, a central plate and a flush surround plate has a protection degree of IP41.
- Marking: CE



170-79090

4 year warranty

Flush-mounting socket ADSL splitter, claw fixing



Flush-mounting socket with screw terminals and claws with RJ11 outlet and ADSL outlet, with claw fixing. This ADSL splitter can also be used for ADSL2, ADSL2+ and VDSL2.

Flush-mounting socket ADSL splitter, claw fixing. The stripping length is around 3 mm. When mounting the socket outlet in a flush-mounting box with grip surfaces, use claws that can be rotated open using screws with a combination screwhead (Pz1 or slot 1 x 5 mm). The claws, which have a depth of engagement of 31 mm, can be manually pushed back into their original position after unscrewing. These claws can also be easily pushed out using a screwdriver. The flush-mounting frame is made from 1 mm-thick metal which is galvanized on all sides after cutting, even on the cut edges. On the horizontal and vertical axes, the flush-mounting frame has 4 grooves for screw mounting in flush-mounting boxes. These grooves have a screw aperture of 7 mm. For mounting on panels, the flush-mounting frame is equipped with 4 screw holes (indicated by a screw symbol) with a diameter of 3 mm. The middle of the flush-mounting frame is indicated (chalk line, laser, ..) in both the horizontal and vertical directions, so that mounting one or more mechanisms can be carried out quickly and easily. The base is equipped on all sides with folded-up dovetails, allowing for both vertical and horizontal coupling (centre-to-centre distance of 71 x 71 mm) of several bases to be carried out quickly and perfectly. The folded-up edges on the outside of the base and their continuation to the inside ensure additional robustness. The flush-mounting frame is equipped, both on the top and the bottom, with a dark grey, plastic end border. This border is made of PC+ASA and is joined to the flush-mounting frame using a melting process. The corners of the two end borders are equipped with rectangular openings (7.9 x 1.5 mm) each containing a multi-positional snap hook. Thanks to the snap hooks, the 4 rectangular openings ensure that the flush surround plate can always be attached flat to the wall, even in cases of untidy plasterwork. This works in two directions: If the flush-mounting box sticks out of the plasterwork, the multi-positional snap hooks can compensate for a 1 to 1.2 mm margin; if the flush-mounting box is sunk too deeply in the plasterwork, the snap hooks can compensate for up to a 1.8 mm margin. The end borders also have 4 round openings that ensure the correct positioning of the flush surround plate in relation to the central plate.

- Protection degree: The combination of a switch, a central plate and a flush surround plate has a protection degree of IP41.
- Marking: CE

