

Twofold faceplate, 60 mm centre distance, vertical, Niko Pure liquid black

242-76200

4 year warranty

Twofold faceplate with 60 mm centre-to-centre distance, vertical, from the range Niko Pure. Niko Pure liquid black

Technical data

Twofold faceplate, 60 mm centre distance, vertical, Niko Pure liquid black.

- Double faceplate for two switches.
- Colour: enamelled liquid black (approximately NCS S 9000 N, RAL 9005)
- Frame composition: It consists of an upper frame and lower frame that are mechanically interconnected.
- Material upper frame: The upper frame is made of hard-coated PMMA.
- Material lower frame: The lower frame is made of dark grey polycarbonate (PC) + acrylic-styrene-acrylate (ASA), black coated.
- Frame thickness: The upper frame is 2 mm thick and the lower frame 6 mm.
- Centre-to-centre distance: 60 mm
- Surface-mounting height: max. 8.5 mm
- Fire safety
 - completely self-extinguishing faceplate
 - complies with a filament test of 650 °C
- Protection degree: IP41 for the combination of a mechanism, central plate and faceplate
- Impact resistance: The combination of a mechanism, a central plate and a faceplate has an impact-resistance of IK06
- Dimensions (HxWxD): 143 x 83 x 8.9 mm
- Certification marks: CEBEC, NF, ÖVE, KEMA
- Marking: CE

