

Threefold faceplate, 71 mm centre distance, Niko Pure alu grey brushed

155-76700

4 year
warranty

Threefold faceplate with 71 mm centre-to-centre distance from the range Niko Pure. Niko Pure alu grey brushed

Technical data

Threefold faceplate, 71 mm centre distance, Niko Pure alu grey brushed.



- Threefold faceplate for three switches.
- Colour: alu grey (approximately NCS S 2002 - G, RAL 000 80 00)
- Frame composition: It consists of an upper frame and lower frame that are mechanically interconnected.
- Material upper frame: The upper frame is made of brushed aluminium.
- Material lower frame: The lower frame is made of dark grey polycarbonate (PC) + acrylic-styrene-acrylate (ASA).
- Frame thickness: The upper frame is 6 mm thick and the lower frame 2 mm.
- Centre-to-centre distance: 71 mm
- Surface-mounting height: max. 8.5 mm
- Fire safety
 - self-extinguishing: complies with a filament test of 650°C
 - halogen-free
- Protection degree: IP41 for the combination of a mechanism, central plate and faceplate
- Impact resistance: The combination of a mechanism, a central plate and a faceplate has an impact resistance of IK06
- Dimensions (HxWxD): 83 x 225 x 8.9 mm
- Dimensions visible (HxWxD): 83 mm
- Certification marks: CE, CEBEC, KEMA, VDE, ÖVE, SEMKO
- Marking: CE

