

Twofold faceplate, 60 mm centre distance, vertical, Niko Pure alu black brushed

224-76200

4 year
warranty

Twofold faceplate with 60 mm centre-to-centre distance, vertical, from the range Niko Pure. Niko Pure alu black brushed

Technical data

Twofold faceplate, 60 mm centre distance, vertical, Niko Pure alu black brushed.

- Double faceplate for two switches.
- Colour: alu black (approximately NCS S 8005 - R50B, RAL 000 20 00)
- Recommended colour central plate: alu black
- Frame composition: It consists of an upper frame and lower frame that are mechanically interconnected.
- Material upperframe: The upperframe is made of anodised aluminium (alu black).
- Material lower frame: The lower frame is made of dark grey polycarbonate (PC) + acrylic-styrene-acrylate (ASA), black coated.
- Frame thickness: The upper frame is 6 mm thick and the lower frame 2 mm.
- Centre-to-centre distance: 60 mm
- Surface-mounting height: max. 8.5 mm
- Fire safety
 - self-extinguishing: complies with a filament test of 650°C
 - halogen-free
- Protection degree: IP41 for the combination of a mechanism, central plate and faceplate
- Impact resistance: The combination of a mechanism, a central plate and a faceplate has an impact-resistance of IK06
- Dimensions (HxWxD): 143 x 83 x 8.9 mm
- Dimensions visible (HxWxD): 143 x 83 x 8 mm
- Marking: CE

