

Photo cell, IP54, variable light sensitivity

Photo cell for outdoor applications (IP54). To be used in combination with the analogue sensor module (550-00230). The photo cell has a variable light sensitivity between 3 and 300 lux, 30 and 3 Klux, 300 and 30 Klux or 600 and 60 Klux.



Photo cell, IP54, variable light sensitivity

Photo cell for outdoor applications (IP54). To be used in combination with the analogue sensor module (550-00230). The photo cell has a variable light sensitivity between 3 and 300 lux, 30 and 3 Klux, 300 and 30 Klux or 600 and 60 Klux.

- power supply voltage: 24 Vdc ± 10%
- output signal: 0 - 10 V
- light sensitivity: 3 - 300 lux, 30 - 3 Klux, 300 - 30 Klux or 600 - 60 Klux
- protection degree: IP54
- ambient temperature: -40 - 50 °C



COMPLETE UNIT



350-10012 Pieces: 10 Detector

Technical data

4 year
warranty

Article number	350-10012
Input voltage	24 Vdc \pm 10 %
Light intensity range	3 lux – 60000 lux
Number of channels	1 channel
Ambient temperature	-40 – 50 °C
Mounting method	surface mounting
Dimensions visible (HxWxD)	50 x 52 x 29,5 mm
Dimensions (HxWxD)	52 x 52 x 29,5 mm
Wire capacity	NA
Protection degree	IP54
Marking	CE