

# Compact, programmable internal video unit surface-mounting, with colour screen and comfort keys

## Function description

This compact, surface-mounting, internal video unit with colour screen is delivered standard equipped to perform the following functions: allow a conversation with a visitor, produce a different tone for a call at an apartment door, main door or an internal call, switch lights on and off, open doors, adjust the volume and image, switch off the ring tone, activate the camera, indicate a busy signal and call signal with LEDs, transmit a control function (for relay 10-831 and others), allow a parallel call, make an internal call, etc.

The controls consist of clear, intuitive comfort keys and a menu which appears on the screen. The communication with the visitor is hands-free. The device can be entirely programmed using the Niko Configuration Software for access control.



## Technical data

Reference number	10-576
Dimensions	186 x 101 x 20 mm (HxWxD)
Finishing colour, material	white (polycarbonate + ABS)
Input current in standby	I(a) = 0.04 mA, I(P) = 13.5 mA
Max. input current	I(Pmax) = 130 mA
Display	TFT screen with 8.9 cm (3.5") diagonal screen size
Wiring	6-wired
Extra terminals	yes (e.g. for connecting door opener)
Protection degree	IP30
Ambient temperature	-5 °C to +40 °C
Marking	CE marking
Conversation mode	possibility of activating simplex/half-duplex conversation mode
Privacy	block listen in and automatic call termination
Extensions	possibility to connect door opener and extra camera
Configuration	Niko configuration software for access control

## Dimensions

