DEMKO CERTIFICATE

Certificate No. D-09152

Page 1/5

Date of Issue 2022-03-17

Certificate Holder NIKO NV

INDUSTRIEPARK WEST 40 SINT-NIKLAAS BE-9100

BELGIUM

Manufacturer NIKO NV

INDUSTRIEPARK WEST 40 SINT-NIKLAAS BE-9100

BELGIUM

Production site NIKO NV

INDUSTRIEPARK WEST 40 SINT-NIKLAAS BE-9100

BELGIUM

Certified Product Switches (for fixed installations)

Model 170-700**+***-61105, 170-700**+***-61901, 170-716**+***-61105, 170-

730**+***-61105, 170-730**+***-61901 See page 2-3 for additional Information

Trademark NIKO

Ratings 6 A, 10 A, 10 AX or 16 AX, 250 Vac, IP20

Tested according to EN 60669-1:2018

Test Report No. 4790109601.1 issued on 2022-02-14

Additional

Expire date 2030-06-29

Certification Manager

Jan-Erik Storgaard

This is to certify that representative sample(s) of the Product described herein ("Certified Product") have been investigated and found in compliance with the Standard(s) indicated on this Certificate, in accordance with the D-Mark Requirements. As specified in the respective appendix below the Designated Certificate holder is entitled to use the D-Mark, or its alternative for cables, for the Certified Product manufactured at the production site(s) identified above, in accordance with the D-Mark Service Agreement, including without limitation the D-Mark string and Certification Services Service Terms. Only those Products bearing the D-Mark should be considered as being covered by UL's D-Mark Service. This Certificate shall remain valid through the expiration date, unless terminated earlier in accordance with the Service Agreement including without limitation if the Standard identified on this Certificate is amended or withdrawn prior the expiration date.

Certification Body

UL International Demko A/S, Borupvang 5A, DK-2750 Ballerup, Denmark, Tel. +45 44 85 65 65, info.dk@ul.com www.UL.com



 Certificate No.
 D-09152

 Page
 2/5

 Date of Issue
 2022-03-17

Additional Model(s):

SCREW TERMINALS

170-711** + ***-61105	pattern 1 + single actuating member, 10AX 250V ~
170-700** + ***-61105	pattern 1 push-button + single actuating member, 10A 250V ~
170-700** + ***-61901	pattern 1 push-button + hotel card actuating member, 10A 250V ~
170-716** + ***-61105	pattern 6 + single actuating member, 10AX 250V ~
170-730** + ***-61105	pattern 6 push-button + single actuating member, 10A 250V ~
170-730** + ***-61901	pattern 6 push-button + hotel card actuating member, 10A 250V ~
170-715** + ***-61505	pattern 5 + double actuating member, 10AX 250V ~
170-712** + ***-61105	pattern 2 + single actuating member, 10AX 250V ~
170-722** + ***-61105	pattern 6/2 + single actuating member, 10AX 250V ~
170-726** + ***-61505	pattern 6+6 + double actuating member, 10AX 250V ~
170-750** + ***-61505	pattern 6 push-button+6 push-button + double actuating member,
	10A 250V ~
170-717** + ***-61105	pattern 7 + single actuating member, 10AX 250V ~
170-759** + ***-65905	pattern 4 + double actuating member, 10AX 250V ~
170-859** + ***-65914	pattern 4 2xpush-button + double actuating member, 10A 250V ~
170-959** + ***-65918	pattern 4 2xpush-button (for electronic controls) + double actuating
	member, 10A 250V ~
170-756** + ***-61505	pattern 6 push-button+6 + double actuating member, 10A 250V ~
170-771** + ***-60005	pattern 1 (control)+ single actuating member, 10AX 250V ~
170-776** + ***-60005	pattern 6 (control)+ single actuating member, 10AX 250V ~
170-712** + ***-63*06	pattern 2 + pull-cord operating mechanism, 10AX 250V ~
170-716** + ***-63*06	pattern 6 + pull-cord operating mechanism, 10AX 250V ~
170-717** + ***-63*06	pattern 7 + pull-cord operating mechanism, 10AX 250V ~
170-730** + ***-63*06	pattern 6 push-button + pull-cord operating mechanism, 10A 250V ~
170-716**(16A) + ***-61105	pattern 6 16A + single actuating member, 16AX 250V ~
170-713** + ***-61105	pattern 2 16A + single actuating member, 16AX 250V ~
170-713** + ***-63*06	pattern 2 + pull-cord operating mechanism, 16AX 250V ~
170-716**(16A) + ***-63*06	pattern 6 + pull-cord operating mechanism, 16AX 250V ~
170-7400*+ Z	pattern 1 push-button, 6A 250V ~



 Certificate No.
 D-09152

 Page
 3/5

 Date of Issue
 2022-03-17

Additional Model(s):

SCREWLESS TERMINALS

170-711**r + ***-61105 170-700**r + ***-61105 170-700**r + ***-61901 170-716**r + ***-61105 170-730**r + ***-61105 170-730**r + ***-61901 170-715**r + ***-61505 170-712**r + ***-61105 170-722**r + ***-61105 170-726**r + ***-61505 170-750**r + ***-61505	pattern 1 + single actuating member, 10AX 250V ~ pattern 1 push-button + single actuating member, 10A 250V ~ pattern 1 push-button + hotel card actuating member 10A 250V ~ pattern 6 + single actuating member, 10AX 250V ~ pattern 6 push-button + single actuating member, 10A 250V ~ pattern 6 push-button + hotel card actuating member 10A 250V ~ pattern 5 + double actuating member, 10AX 250V ~ pattern 2 + single actuating member, 10AX 250V ~ pattern 6/2 + single actuating member, 10AX 250V ~ pattern 6+6 + double actuating member, 10AX 250V ~ pattern 6 push-button+6 push-button + double actuating member, 10A 250V ~
170-717**r + ***-61105 170-759**r + ***-65905 170-859**r + ***-65914 170-959**r + ***-65918	pattern 7 + single actuating member, 10AX 250V ~ pattern 4 + double actuating member, 10AX 250V ~ pattern 4 2xpush-button + double actuating member, 10A 250V ~ pattern 4 2xpush-button (for electronic controls) + double actuating member, 10A 250V ~
170-756**r + ***-61505 170-771**r + ***-60005 170-776**r + ***-63*06 170-712**r + ***-63*06 170-716**r + ***-63*06 170-717**r + ***-63*06 170-730**r + ***-63*06 170-713**r + ***-61105 170-713**r + ***-61105 170-713**r + ***-63*06 170-716**r(16A) + ***-63*06	pattern 6 push-button+6 + double actuating member, 10A 250V ~ pattern 1 (control) + single actuating member, 10AX 250V ~ pattern 6 (control) + single actuating member, 10AX 250V ~ pattern 2 + pull-cord operating mechanism, 10AX 250V ~ pattern 6 + pull-cord operating mechanism, 10AX 250V ~ pattern 7 + pull-cord operating mechanism, 10AX 250V ~ pattern 6 push-button + pull-cord operating mechanism, 10A 250V ~ pattern 6 16A + single actuating member, 16AX 250V ~ pattern 2 16A + pull-cord operating mechanism, 16AX 250V ~ pattern 2 16A + pull-cord operating mechanism, 16AX 250V ~ pattern 6 16A + pull-cord operating mechanism, 16AX 250V ~




Certificate No. D-09152 Page 4/5

Date of Issue 2022-03-17

Certification Mark D-Mark

The D-Mark, as displayed below, shall appear on certified products only. Except as specified below the Mark shall be legible and no Minimum size is specified.



The size of the Mark may be reduced or enlarged on the condition that it remains readable and that the proportions of width and height are kept. The use of dark text for the D-Mark on light backgrounds and light text on dark backgrounds is permitted.

The D-Mark may appear on a label, nameplate, or may be cast, stamped or molded into the product. When appearing on a label or nameplate, the Manufacturer's name or trademark along with a model number are also required on that same label or nameplate. If cast, stamped or molded, the Certificate Manufacturer's name or trademark and model number shall also appear elsewhere on the product

When putting the product on the EU market, the manufacturer's name, trademark or mark of origin must be affixed in a clearly visible location and position on the product, on the package and in the user manual. It can be affixed by label, be directly imprinted, or cast or molded into the product.

Where the size of the product does not allow the Mark, the manufacturer's name, trademark, mark of origin and model number to be legible, and appearance on a label is not desired, it is allowed to cast, stamp or mold the Mark into the product, in a size which is not visible to the naked eye, provided the legible Mark, the manufacturer's name, trademark or mark of origin and model number appears on the package and in the user manual





Certificate No. D-09152
Page 5/5
Date of Issue 2022-03-17

Alternate certification Mark for cables

As an alternative to the D-Mark specified above the alternate D-Mark, displayed below, can appear on certified cables only. Minimum size is not specified, as long as the mark is legible.

⊲DEMKO⊳

The alternate D-Mark may be cast, stamped or molded into the cable and continue throughout the length of the cable as specified in the applicable cable standard.

All content shall be in accordance with the details provided on this D-Mark Certificate.

