

Twilight switch, 24 V, one channel, 4 A, 2 - 200 lux

Twilight switch for outdoor wall mounting (IP54), suitable for switching outdoor lighting. To be used in combination with the digital potential-free sensor module (550-00210). Large sensor surface for accurate light measuring. In conformity with the European directive for EMC and safety EN60669-2-1.



Twilight switch, 24 V, one channel, 4 A, 2 - 200 lux

Twilight switch for outdoor wall mounting (IP54), suitable for switching outdoor lighting. To be used in combination with the digital potential-free sensor module (550-00210). Large sensor surface for accurate light measuring. In conformity with the European directive for EMC and safety EN60669-2-1.

- power supply voltage: 24 Vac/Vdc \pm 10%
- relay contact: NO (max. 4 A)
- incandescent lamps: 40 W
- hysteresis on light sensitivity: + 50%
- switch-off delay: \pm 1 min
- light sensitivity: 2 - 200 lux
- protection degree: IP54
- operating temperature: -50 - 50 °C
- dimensions: 102 x 73 x 39 mm (HxWxD)



COMPLETE UNIT



350-10032

Pieces: 5


Twilight switch

Technical data

4 year
warranty

Article number	350-10032
Input voltage	24 Vac/Vdc \pm 10 %
Relay contact 1	NO (max. 4 A), potential-free
Light intensity range	2 lux – 200 lux
Number of channels	1 channel
Ambient temperature	-50 – 50 °C
Mounting method	surface mounting
Dimensions visible (HxWxD)	50 mm
Dimensions (HxWxD)	108 x 50 mm
Wire capacity	NA
Protection degree	IP54
Marking	CE

Dimensions



Wiring diagram

