

Functions

Explore endless possibilities via one simple solution

		DETECTORS					
Type		230 V motion detectors	1 channel 230 V presence detectors	2 channels 230 V presence detectors	DALI standard	DALI comfort	DALI BMS
INPUT	Inputs or push-buttons	0	1	2	1	4	
	Free assignment of push-buttons			●		●	
	Wireless push-button for override of lighting control					Only comfort wireless	
	External trigger (activation via external systems)					●	
	Wired slave		●	●	●	●	
	External input devices via DALI bus						●
FUNCTIONS	Automatic on/off	●	●	●	●	●	
	Semi-automatic on/off (manual on/off + auto off)		●	●	●	●	
	Daylight control (dimming - based on daylight)				3 zones	4 zones	
	DALI Broadcast + DALI Addressable				●	●	
	Wireless master-to-master link via Bluetooth					●	
	Wireless slave-to-master link via Bluetooth		●	●			
	Multizone - smart board lighting					●	
	2-level control - perfect for corridors					●	
	Turn-on level					●	
	Orientation light				●	●	
	Light scenarios - define and control scenarios					●	
	Folding door function - Wireless sync of lighting control					●	
	Control light in adjacent areas / corridors					●	
	Tunable white third-party integration				●	●	
	Tunable white dynamic and presets					●	
	Output relay - control HVAC / standby minimisation / light					●	
	External relay for HVAC / standby minimisation					●	
	BMS integration				●	●	●
	Event log	●	●	●	●	●	●
Cloud solution for documentation, backup and distribution of configuration files	●	●	●	●	●	●	
Settings and configuration can be locked with a PIN-code	●	●	●	●	●	●	
APP	DALI command monitor				●	●	
	Software update of detector via app	●	●	●	●	●	●
	2-way Bluetooth communication	●	●	●	●	●	●